



Basic Information

Place of Origin: China

. Brand Name: skymen/OEM CE/ISO9001:2008 · Certification: JP-360ST Model Number: • Minimum Order Quantity: 1 unit • Price: Negotiation Packaging Details: wooden case • Delivery Time: In Stock Payment Terms: L/C, T/T,paypal



Product Specification

. Supply Ability:

Material: Stainless Steel SUS

500 units per week

• Capacity: 135L

Tank Size: 600*500*450 MmUnit Size: 805*705*780 Mm

Frequency: 40 KHz
Ultrasonic Power: 1800 W
Heating Power: 4500w
Timer: 1-99 Minutes

• Heater: 20~95C Adjustable

Highlight: ultrasonic washing machine,
ultrasonic cleaning unit



Product Description

130 Liters Anti Rust Industrial Ultrasonic Cleaner SS Hood Filters And Stove Parts Cleaning

Function:

Ultrasound is the most efficient and cost effective method of removing Carbon and FOG (Fats, Oils & Grease). Restaurants, Hotels, Bakeries, Supermarkets and other Commercial kitchens depend on this state of the art technology for the ultimate cleaning power, for reducing utility bills, lowering kitchen overhead, increasing productivity and providing a meaningful Return on Investment.

It used in Commercial Kitchens and Bakeries to clean Carbon Build up and F.O.G. (Fats, Oils & Grease) from equipment including aluminum baking pans, hood filters, baking racks, floor mats and more

Features:

Dirt and oil could be removed in a short time by using the strong cavitation of ultrasound.

Time is adjustable among 1 second to 500 hours by simple handle of large timer.

Additional special case for small parts cleaning and drainage for changing of cleaning solution.

Automatic stopwatch to manage working time and maintenance time.

Standard residual-current circuit breaker: used for testing leakage power. And keeping moving of machine and cutting of power switch.

Specificatoin:

Specificatorii.	LID COOOT
Model	JP-360ST
Ultrasonic	1800W (30pcs transducers)
power	
Frequency	40KHz
Housing	SUS304
material	
Tank material	SUS304
Heating power	1800W
Tank capacity	135 L
Timer	Digital 1-99 min adjustable
Heater	0~80°C
Voltage	AC 100~120V, 60Hz
	AC 220~240V, 50Hz
Tank size	700*500*450 MM
Unit size	805*705*780 MM
Packing size	Wooden case
N.W.	85 Kg
G.W.	110 Kg
Certificate	ISO9001:2008 CE & RoHS

From 10 galles to 200 gallons ,size could be customized



- 1* basket
- 1* generator;

How to use an ultrasonic cleaner?

Directions for use

Step 1



Fill the with (preferably hot) water to the 'Fill Line' marked on the inside, plug the tank into an electrical outlet, and switch ON

Step 2



Slowly add the oil/Carbon-Removal Powder

Step :



Load the tank with your dirty pots, pans, vent hood filters into the tank and Close the lid, leaving the items in the tank to soak, and walk away!

Step 4



Remove the items from the tank, then simply rinse off any loose or softened carbon fragments.



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen