

## 15L Table Top Large 360W Ultrasonic Cleaner Ultrasonic Surgical Instrument Cleaning Bath JP-060S

Our Product Introduction

for more products please visit us on [skymenultrasonic.com](http://skymenultrasonic.com)

### Basic Information

- Place of Origin: China
- Brand Name: Skymen
- Certification: CE ROHS REACH
- Model Number: JP-060S
- Minimum Order Quantity: 1 unit
- Price: Negotiation
- Packaging Details: 1 unit per carton, carton size: 340\*250\*310mm
- Delivery Time: In Stock
- Supply Ability: 8000 pcs per month



### Product Specification

- Tank Inner Size: 330 X 300 X 150mm(L\*W\*H)
- Model: JP-060S
- Material: SUS304
- Ultrasonic Power: 360W
- Heating Power: 300W
- Ultrasonic Frequency: 40khz
- Heater: 20~80 Degree Celsius
- Timer: 1~30 Minutes
- Plug: USA Standard, Eu Standard, UK Standard
- Power Supply: AC 110V ; AC220V
- Highlight: **ultrasonic bath cleaner, table top ultrasonic cleaner**



### More Images



## Product Description

### Table Top Large Ultrasonic Cleaner Ultrasonic Surgical Instrument Cleaning Bath

#### Features:

Sensitive touch control panel  
 Touch-Sensitive Control display  
 20 degree tilted design  
 more convenient for operation  
 stainless steel tank has resistance to wear and long work life.  
 tank capacity: 15L(3.6gallon), with digital timer & heater control  
 with Stainless steel basket  
 Use just tap water, or industrial alcohol and solvent cleaner for more higher cleaning requirement  
 industrial control chip microcontroller. flexible circuit boards control, more secure & stable  
 temperature adjustable from 20°C to 80°C




#### JP-060S product specification:

Ultrasonic frequency	40,000Hz
Material of tank	SUS304
Material of shell	SUS304
Capacity	15L
Timer	digital control, 0~30 mins
Heater	digital control, 20°C to 80°C
Power supply type 1	AC 100~120V, 50/60Hz
Power supply type 2	AC 220~240V, 50/60Hz
Ultrasonic power	360W
Heating Power	300W
Tank inner dimension	330x300x150mm
Unit dimension	360*325*285mm
Packing size	460*410*360mm
N.W.	9.1kg
G.W.	10.3kg

# New upgrade new experience

The new upgrade is only for your better experience



## How to Use an Ultrasonic Cleaner for Medical & Surgical Instruments

Medical and surgical instruments in a variety of sizes and complexity can pose challenges when it comes to cleaning, disinfecting and sterilizing them after use. An ultrasonic cleaner is an ideal tool for the first step in this three step process to protect medical personnel and patients from possible infection due to pathogens that remain on the instruments after a procedure.

### Suggested Ultrasonic Cleaning Procedure

In all cases manufacturers' instructions should be followed when using an ultrasonic cleaning process. These are representative steps.

Fill the ultrasonic cleaning tank with an approved medical instrument cleaning solution such as CLN-LR012 available from Tovatech following dilution instructions provided. Turn the cleaner on to start the degassing process. This step removes entrained air in new solutions that interferes with the efficiency of cavitation and takes approximately 10 minutes.

In the meantime:

Segregate instruments by alloy or composition to avoid potential damage (Chromium plated instruments should not be cleaned ultrasonically)

Instruments with movable parts should be disassembled to facilitate cleaning

Place the instruments in the ultrasonic cleaner's mesh basket, taking care that they do not come in contact with each other

Cannulated or lumened instruments should be positioned to insure interiors are wetted with the cleaning solution. In some instances placing them on an angle will facilitate this


Set the control panel per manufacturers' instructions and start the cleaning process

At the end of the cycle, remove the instruments from the ultrasonic cleaning bath and thoroughly rinse them to remove all traces of the cleaning solution. Deionized water rinses will avoid spotting. If the instruments are not to be immediately disinfected and sterilized be certain that they are thoroughly dried and protected. Part reassembly can occur after sterilization.

Procedures should be in place to guide the replacement of used ultrasonic cleaning solutions. In some instances it is recommended that solution be drained and tanks thoroughly cleaned and dried after each ultrasonic cleaning cycle. Most solutions available today are biodegradable, which facilitates disposal but local authorities should be consulted on proper practices.







## APPLICATION



Lab ware    Hardware    Jewellery    Denture    Fruit    Glasses

The ultrasonic cleaner uses ultrasonic waves (vibration) using water with detergents or enzymatic products to break up soil and organic material on medical instruments/devices. These devices are rinsed then autoclaved (sterilized). The autoclave sterilizer uses heat, steam, and pressure to kill all pathogenic microorganisms and their spores.

### Package Includes:

- 1 x Digital Ultrasonic Cleaner
- 1 x Cleaning Basket
- 1 x Manual



**Skymen Technology Corporation Limited**



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen