PCB Board / Electronic Parts Benchtop Ultrasonic Cleaner 6.5L 180W

Adjustable Timer

Basic Information

Place of Origin: Shenzhen, China

• Brand Name: Skymen

• Certification: RoHS, CE, FCC, SGS

Model Number: 031S Minimum Order Quantity: 1

Price: Negotiation
Packaging Details: Wooden case
Delivery Time: In Stock
Payment Terms: T/T

• Supply Ability: 8000 pcs per month



Product Specification

Model: 031SFirst Tank Volume: 6.5L

• Tank Size: 300*150*150mm

Ultrasonic Power: 180WHeating Power: 200WFrequency: 40KHz

Timer: 0~30 Minutes Adjustable
 Temperature: 20~80°C Adjustable
 Highlight: ultrasonic bath cleaner, table top ultrasonic cleaner



More Images



Product Description

6.5L Ultrasonic Cleaner 180W for PCB board, electronic parts, TV parts, computer parts 40KHz

Specification

Model	031S		
Ultrasonic frequency	40,000Hz		
Material of tank	SUS304		
Material of shell	SUS304		
Capacity	6.5L		
Timer	0~30 mins adjustable		
Temperature	20~80°C adjustable		
Power supply type 1	AC 100~120V, 50/60Hz		
Power supply type 2	AC 220~240V, 50/60Hz		
Ultrasonic power	180W		
Heating Power	200W		
Tank inner dimension	300*150*150mm		
Unit dimension	375*200*275mm		
Packing size	410*255*360mm		
N.W.	5.85kg		
G.W.	6.6kg		
Warranty	1 year		
Certificate	SGS & FCC & CE & RoHS		

Similar models with different capacity: Stainless Bench Top



Capacity	Tank Size	Ultrasonic Power	Heating Power	Frequency
(L)	(L*W*H)mm	(W)	(W)	(KHz)
0.8	150*85*65	35	0	40
0.9	150*135*65	60	100	40
2	150*165*100	60	100	40
3.2	240*135*100	120	100	40
4.5	300*150*100	180	200	40
6.5	300*150*150	180	200	40
10	300*240*150	240	200	40
15	330*300*150	360	300	40
22	500*300*150	480	500	40
30	500*300*200	600	500	40
	(L) 0.8 0.9 2 3.2 4.5 6.5 10 15	(L) (L*W*H)mm 0.8 150*85*65 0.9 150*135*65 2 150*165*100 3.2 240*135*100 4.5 300*150*150 10 300*240*150 15 330*300*150 22 500*300*150	Capacity Tank Size Power (L) (L*W*H)mm (W) 0.8 150*85*65 35 0.9 150*135*65 60 2 150*165*100 60 3.2 240*135*100 120 4.5 300*150*100 180 6.5 300*150*150 180 10 300*240*150 240 15 330*300*150 360 22 500*300*150 480	Capacity Tank Size Power Heating Power (L) (L*W*H)mm (W) (W) 0.8 150*85*65 35 0 0.9 150*135*65 60 100 2 150*165*100 60 100 3.2 240*135*100 120 100 4.5 300*150*100 180 200 6.5 300*150*150 180 200 10 300*240*150 240 200 15 330*300*150 360 300 22 500*300*150 480 500

Image:



















Compared to traditional cleaning methods, ultrasonic cleaners show great advantages. Especially in specialized and grouporiented production enterprises, ultrasonic cleaning has gradually replaced traditional dipping, brushing, pressure washing, vibration cleaning and steam cleaning.

Ultrasonic cleaners are highly efficient and clean, thanks to the penetrating and cavitation shock waves that their sound waves travel through the medium. Therefore, it is easy to clean the parts with complicated shapes, and the general degreasing, descaling, phosphating and other processes can be completed in two or three minutes under the action of ultrasonic waves, and the speed can be several times higher than the conventional method. To a few dozen degrees, the cleanliness can also reach a high standard, which highlights the results that are difficult or impossible to replace with other treatment methods in many cases where the surface quality and production efficiency of the product are high.



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen