

Wax In Wafer Ultrasonic Cleaning Machine 77 Liter With 3000W Heating **Power**

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

SKYMEN / OEM CE/FCC/RHoS/REACH JP-240ST

500 units per week

- 1 unit
 - Negotiation
 - wooden case

China

- In Stock
- T/T, L/C, Paypal



Product Specification

- Model:
- Material:
- Tank Capacity:
- Tank Size:
- Transducer:
- Ultrasonic Power:
- Heating Power:
- Timer:
- Heater:
- Frequency:
- Highlight:
- SUS 304/316 77L 550*400*350 Mm 24pcs 1200W 3000W 1-99 Minutes Adjustable 20~95C Adjustable

JP-240ST

- 40KHz / 28KHz
 - dual frequency ultrasonic cleaner, ultrasonic washing machine



Our Product Introduction

Product Description

Wax in Wafer Ultrasonic Cleaning Machine 77 Liter with 3000W Heating Power

Notes on the use of ultrasonic cleaning machine:

1. When the heating is turned on, do not let the solution fall below 2cm from the upper limit, otherwise it will cause damage to the sensor or heater;

When the washing machine is running, do not put your hand into the water tank. Will cause discomfort or skin irritation;
Regularly change the cleaning liquid depending on the degree of fouling of the cleaning liquid, and do not make the

3. Regularly change the cleaning liquid depending on the degree of fouring of the cleaning liquid, and do not make the temperature of the liquid exceed 45 ° C;

4. Do not place instruments or containers directly on the bottom of the cleaning water tank, they should be placed in the tray rack;

Do not use chlorine-containing bleaching cleaning solution, do not use acidic materials, which may damage the water tank;
Do not use ethanol, gasoline or other flammable cleaning solutions. Otherwise it will cause fire and explosion, and use water-based solution;

7. If the washing machine is not used for a long time, please turn off the power switch when the machine is stopped, drain the cleaning liquid, and keep the machine clean;

8. The lid of the ultrasonic cleaner should be covered when cleaning to prevent the generation of deep gas glue;

Specificatoin:

JP-240ST
40KHz / 28KHz
SUS304
SUS304 / 316
24pcs
1200W (12pcs transducers)
3000W
77L
Yes
Digital 1-99 min adjustable
0~95°C
AC 100~120V, 60Hz AC 220~240V, 50Hz
500*400*350 mm
840*655*885 mm
Wooden case
85 Kg
95 Kg
ISO9001:2008 CE & REACH
00 gallons ,size could be customize

Features:

Fully insulated stainless steel tank construction; Digital LED screen show temp and time, easy to use; Adjustable built-in heat to improve the cleaning effectiveness; Stainless steel lid help to reduce the noise;

The whole set machine including:

1* cleaning machine

1* lid

1* basket

1* manual

Model	Tank size	Volume	Ultrasoni c Power	Heating Power	Transducer
	L*W*H (mm)	(L)	(W)	(W)	(pcs)
JP-120ST	500X300X25 0	38L	600W	1500W	12pcs
JP-180ST	500X350X30 0	53L	900W	1500W	18pcs
JP-240ST	550X400X35 0	77L	1200W	3000W	24pcs
JP-300ST	550X450X40 0	99L	1500W	4500W	30pcs
JP-301ST	800X300X40 0	96L	1500W	4500W	30pcs
JP-360ST	600X500X45 0	135L	1800W	4500W	36pcs
JP-480ST	700X500X50 0	175L	2400W	6000W	48pcs
JP-600ST	800X600X55 0	246L	3000W	6000W	60pcs


Similar models with different tank volume:

JP-720ST	1000X600X6 00	360L	3600W	9000W	72pcs
JP-1108ST	1000X900X6 00	540L	5400W	18000W	108pcs
JP-1144ST	1200X1000X 800	960L	7200W	27000W	144pcs


How does Ultrasonic Cleaner work?

DIRT ELIMINATION PROCESS THROUGH ULTRASONIC TECHNOLOGY

 Cleaning effect will be much better if using the machine together with proper solvent.







As ultrasonic wave through the solution in the tank, cause alternating high and low pressures in the solution.

During the low pressure stage, millions of microscopic bubbles form and grow. This process is called "CAVITATION".

During the high pressure stage, the bubbles implode releasing enormous amounts of energy. They work in all directions, attacking surface and invading all recesses and openings.

Cleaning effect:







After





