

Shenzhen, China

RoHS, CE, FCC, REACH

Skymen

JP-010

Negotiation

In Stock

Wooden case

8000 pcs per month

1

60W SUS304 Benchtop Ultrasonic Cleaner 40KHz FCC For Dental Clinic

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T
- Supply Ability:



Product Specification

 Highlight: 	60W SUS304 Benchtop Ultrasonic Cleaner, SUS304 Benchtop Ultrasonic Cleaner 40KHz, FCC Dental Ultrasonic Cleaner
• Temperature:	20~80°C Adjustable
• Timer:	0~30 Minutes Adjustable
Frequency:	40KHz
 Heating Power: 	100W
Ultrasonic Power:	60W
• Tank Size:	150*135*100mm
• Tank Volume:	2L
• Model:	JP-010

Ultrasonic Cleaning Machine 40KHz for Dental Instruments Dental Clinic 2L

The ultrasonic cleaning machine uses the so-called air effect generated by the high-frequency oscillation signal emitted by the ultrasonic wave, which causes the liquid to flow and generate tens of thousands of tiny bubbles. This is the strong growth and closing effect of the micro bubbles with the ultrasonic vibration. Generates huge impact pressure. (Approximately 100 atmospheres) This huge impact pressure acts on the surface of the object to be washed, and the dirt is emulsified and dispersed, leaving the object to be cleaned.

In terms of dentistry, since mobile phones, pliers, burs, etc. are directly applied to different patients, it is necessary to perform high-temperature and high-pressure disinfection after cleaning. The ultrasonic cleaning machine removes the dirt in the pipes and bucket clamps, thus The mobile phone can avoid the problem of reducing the service life during the high-temperature and high-pressure disinfection to the greatest extent.

So what kind of ultrasonic cleaning machine should dentistry choose? We believe that the following points should be noted: 1. With heating function;

2. Able to work continuously (good ultrasonic cleaner can work 3 times continuously for 30 minutes)

JP-010 Specification:

Ultrasonic frequency	40,000Hz	
Material of tank	SUS304	
Material of shell	SUS304	
Capacity	2L	
Timer	0~30 mins adjustable	
Temperature	20~80°C adjustable	
Power supply type 1	AC 100~120V, 50/60Hz	
Power supply type 2	AC 220~240V, 50/60Hz	
Ultrasonic power	60W	
Heating Power	100W	
Tank inner dimension	150*135*65mm	
Unit dimension	175*160*175mm	
Inner Packing size	255*240*230mm	
Big carton for 12pcs	525*500*485mm for 8pcs	
N.W.	2kg	
G.W.	2.5kg	
Certificate	ISO9001:2008 & CE & RoHS	

JP-010 2.0L









