

Guangdong China

CE,RoHS,ISO

Skymen

JP-031S

Negotiation

In Stock T/T

5000000pcs/month

1pc/Carton Single package size:

350*260*350 mm (L x W x H)

1

SUS304 Tank Benchtop Ultrasonic Cleaner 6.5 Liters 40KHz With Degas Semi Wave Function

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Doon

Product Specification

- Frequency:
- Tank Capacity:
- Timer:
- Heater:
- Voltage (v):
- Ultrasonic Power:
- Heating Power:
- Highlight:

40KHz 6.5L

0.01
1-30minutes , Digital Timer
20°C To 80°C

- 110.220
- 90W/180W Adjustable
- 200 W, Digital Heating
- SUS304 Tank Benchtop Ultrasonic Cleaner, Benchtop Ultrasonic Cleaner 6.5 Liters, 90W ISO Table Top Ultrasonic Cleaner



More Images



for more products please visit us on skymenultrasonic.com

6.5 liters bench top ultrasonic cleaner SUS304 tank with degas and semi-wave function for Lab

How does an ultrasonic cleaner?

This is a method of cleaning both sweet and powerful.

Ultrasound form of pressure variations that propagate through the material immersed in a liquid. These high-frequency vibrations produce millions of tiny microscopic bubbles whose characteristic is to implode immediately, releasing high energy causing the detachment of impurities even in inaccessible corners. Meanwhile, the collapse of these bubbles generates movements in the bath, conducive to cleaning.

Water can get inside all crevices, every corner, every even the smallest cavities, the ultrasonic cleaner can clean complex parts and remove small particles that can not be cleaned by hand

This gentle cleaning method completely eliminates all impurities, dirt, oxidation, oil, grease, carbonized deposits and contaminants from all surfaces of objects that are in contact with the cleaning liquid.

Specifications:

specifications.							
Ultrasonic Frequency	40,000 Hz						
Material	Stainless Steel SUS304						
Tank Capacity	6.5 L						
Timer	1-30minutes , Digital timer						
Heater	20°C to 80°C						
Power Supply	AC 100 ~ 120V, 50 / 60Hz						
	AC 220 ~ 240V, 50 / 60 Hz						
Ultrasonic Power	180W/90W adjustable						
Heating Power	200 W, Digital Heating						
Tank Size	300 x 150 x 150 mm (L x W x H)						
Unit Size	325 x 180 x 225 mm (L x W x H)						
Package Size	410 x 255 x 350 mm (L x W x H)						
N.W.	5.5 kg						
G.W.	6.5 kg						

1. Lower noise. The lid fully sealed, reduce noise

2. tank capacity:6.5L, with Digital timer & heater control

3.Use just tab water, or industrial alcohol and solvent cleaner for more higher cleaning requirement

4. industrial control chip microcontroller. flexible circuit boards control, more secure & stable

5.New update and tilted touch control panel, angle of 20 degree tilted, user-friendly easy operation

6,With degas function and have semiwave mode,with degas function to prevent oxidation

7, The heat dissipation is very good, update 3D heat radiating system, fast heat dissipation

8, The handle is anti-static anti-high temperature, not slippery hand, more security

9,Use imported brand transducer, the strength of cavitation get stronger, the cleaning effect gets even better

10, The tank Adopt industrial high quality SUS 304, thicken tank fromed by one time stamping without welding, with good corrosion resistance, heat resistance, seamless leak-proof

11,Stainless steel drain valve, the water outlet is made of high-quality stainless steel, corrosion-resistance and switch adjustable 12, Filtered drain holes, the drainage hole of cleaning machine increase the filter screen, convenient user to cleaning small parts to provent the parts from entering the drainage hole that cause unpressary lesses

parts, to prevent the parts from entering the drainage hole that cause unnecessary losses.

13,1 year warranty, and parts free to send for fix.

14, FCC CE ROHS ISO9001 SGS certification

Digital timer&heater adjustable with degas series											
Model	JP- 020S	JP- 030S	JP- 031S	JP- 040S	JP- 050S	JP- 060S	JP- 070S	JP- 080S	JP- 100S	JP- 120S	
Capacity(L)	3.2	4.5	6.5	10	14.5	15	20	22	30	38	
Tank	240*18	300*15	300*15	300*24	300*24	330*30	330*30	500*30	500*30	500*30	
size(MM)	5*230	0*100	0*150	0*150	0*150	0*150	0*200	0*150	0*200	0*250	
Packing	270*18	330*20	375*20	380*29	370*27	400*35	400*30	585*33	585*32	680*45	
size(MM)	5*230	0*235	0*275	0*280	0*325	0*280	0*200	0*280	7*333	0*450	
Frequenc y(KHz)	40KHz										
Ultrasonic power (W)	120/60	180/90	180/90	240/12 0	300/15 0	360/18 0	420/21 0	480/24 0	600/30 0	720/36 0	
Heating power(W)	100	200	200	200	200	300	300	500	500	800	
Timer(min 0-30 minutes											
Heater(° C)	20-80° C										
Tank Material											

Application:



Packing: Ultrasonic bath*1 Stainless steel basket*1 Lid*1 Power cord*1 English manual*1

PRODUCT PACKAGING Skymen ✓ Cleaning bath ✓ Cleaning basket ✓ Instruction manual 8888 . 3388 0 0 = 0 0 Power cord TRASONIC CLEANER Skymen table top ultrasonic cleaner drawing: Constructure Chart skymen Sk C C H 0 Valve 1 Ultrasonic transducer 0 Panel 2 PCB







e skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen