

China

Skymen

CE ROHS FCC

Negotiation

In Stock

060, JP-080, JP-100

8000 pcs per month

40KHz 30L SUS304 Mechanical Ultrasonic Washer With Timer

JP-010, JP-020, JP-030, JP-031, JP-040, JP-

1 unit per color box, 8 units per big carton

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 unit
- Price:
- Packaging Details:
- Delivery Time:
- Supply Ability:



Product Specification

- Model:
- Capacity:
- Timer:
- Frequency:
- Material:
- Power Supply:
- Materials:
- Heating:
- Highlight:
- JP-010,JP-020,JP-030,JP-031,JP-040,JP-060,JP-080,JP-100 2L,3.2L,4.5L,6.5L,10L,15L,22L,30L 0-30 Minutes Adjustable 40KHz SUS304 AC 110V ; AC 220V SUS 304 20-80 Degree Adjustable

SUS304 Mechanical Ultrasonic Washer,

40KHz Mechanical Ultrasonic Washer, 30L Ultrasonic Bath Cleaner



More Images



Product Description

SUS 304 Ultrasonic Washer 40KHz Ultrasonic Bath Cleaner with timer and heater

Specification:

Model: JP-010/JP-020/JP-030/JP-031/JP-040/JP-060/JP-080/JP-100 Tank Capacity:2L/3.2L/4.5L/6.5L/10L/15L/22L/30L Ultrasonic Frequency:40, 000 Hz Time Setting: 0 - 30 minutes Temperature Setting: Normal-80 degrees Celsius Tank Material:Stainless Steel SUS304

Power Supply:AC 220 ~ 240V, 50 Hz or 110V ~130V 60HZ
 Plug type:EU/UK Plug/USA plug or as your request

Package Included: 1x Ultrasonic Cleaner tank

1x Power cord

1x Clean Basket 1x Manual

1x hose for drainage

Mode I	JP- 010		JP-020	JP-030	JP-031	JP-040	JP-060	JP-080	JP-100
Tank capac ity	2L		3.2L	4.5L	6.5L(with drainage)	10.8L (with drainage)	· ·	22L (with drainage)	30L (with drainage)
Tank size(mm)	150*135*1 00		240*135* 100	300*150*1 0)	300*150* 150	300*240* 150	330*300* 150	500x300x1 50	500*300*20 0
Unit size(mm)	175*160*2 10			325*180*2 25	325*180* 280	325*265* 280		530*325*2 85	530*325*28 5
Box packi ng	255*240*2 65		340*245* 310			435*360* 350		635*405*3 35	635*405*39 0
Ultras onic powe r	60W		120W	180W	180W	240W	360W	480W	600W
Heati ng powe r	100W		100W	200W	200W	200W	300W	500W	500W
Timer	1~30min adjustable		1~30min adjustabl e	1~30min adjustable	1~30min adjustable	1~30min adjustabl e		1~30min adjustable	1~30min adjustable
	0 ~80°C adjustable		0 ~80°C adjustabl e	0 ~80°C adjustable	0 ~80°C adjustable	0 ~80°C adjustabl e		0 ~80°C adjustable	0 ~80°C adjustable
Frequ ency	40,000Hz		40,000Hz	40,000Hz	40,000Hz	40,000Hz	40,000Hz	40,000Hz	40,000Hz
	2.4kg / 2.8kg		3.6kg / 4.3kgs	U V	5.4kg / 6.2kg	7.3kg / 8.4kg	9.1kg / 10.3kg	12.6kg / 14kg	15kg / 16kg

Mechanical Version Product Parameters

Model	0-0 ⁶	0.0	0-0 8	0.0		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0.0
	JP-020	JP-030	JP-031	JP-040	JP-060	JP-080	JP-100
Capacity (L)	3.2L	4.5L	6.5L	10L	15L	22L	30L
Tank Size (mm)	240*135*100	300*150*100	300*150*150	300*240*150	330*300*150	500*300*150	500*300*200
Overall Size (mm)	270*185*230	330*200*235	375*200*275	380*290*280	400*350*280	585*330*280	585*327*333
Ultrasonic Power	120W	180W	180W	240W	360W	480W	600W
Heating Power	100W	200W	200W	200W	300W	500W	500W
Transducer Quantity	2pcs	3pcs	3pcs	4pcs	6pcs	8pcs	10pcs
Time Setting	0-30min	0-30min	0-30min	0-30min	0-30min	0-30min	0-30min
Temperature Setting	up to 80°C	up to 80°C	up to 80°C	up to 80°C	up to 80°C	up to 80°C	up to 80°C
With Drainage Tap	NO	NO	YES	YES	YES	YES	YES
With Cleaning Basket	YES	YES	YES	YES	YES	YES	YES
Tank Materials	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304

Suggested applications:

1. Scientific lab:Eyeglass Frames,Lab Glassware,Optical &Contact Lenses,Pipettes,Test Tubes

2. Electronics Manufacturing:Capacitors,Ceramic Substrates,PC Boards,Packaging Components,SMDs

3. Medical &Dental Labs,Burs,Blood Oxygenators,Cannulae,Dental Instruments,Syringe Parts


4. Jewelry Manufacturing: Chains, Charms, Coins, Intricate Settings, Precious Metals& Gemstones

5. In Auto Industry:Carburetor,Castings,Fuel Injectors,Machined Parts,Stamped Parts,Switches

Product details:

PRODUCT DETAIL

SKYMEN specialize in ultrasonic cleaners manufacturing since 2007, Professional team, quality assurance





Cooling vents

Quickly cool the internal components of the machine, protecting the circuit board.



Insulation handle design, anti-static, anti-high temperature, not slippery hand, more secure.





3

Double insurance

Independent switch operation safety, built-in spare fuse, double insurance.



Thickness 1.1mm, heat-resisting and corrosion-resisting, safety and health







Non-slip pad

Non-slip anti-shock pad, place all surfaces without sliding

Our service:

1.Warranty:

12 months warranty for Skymen ultrasonic cleaner.

If any technical problem during warranty time, replacement parts will be sent free of charge.

Technical support is also available in whole time.

2.Our Advantage:

1. Reply your enquiry in 24 working hours.

2. Experienced staffs answer all your questions in fluent English.

3. OEM is available if the quantity is large.

4. We offer very competitive for all our products.

3.After-sales

Our ultrasonic cleaning equipment undergo an extensive and strict testing and quality control procedure, ensuring every item purchased meet global quality standards.

♦Payment Methods♦

These payments of T/T,Western Union,Paypal are accepted. If you have any problem with the payment, please leave a message to us. Logistics

Logistics

DHL, EMS and Fedex are our choices. If you prefer other reliable shipping company, please leave a message to us.

♦Tracking Number♦

Tracking number will be informed within 2-3 work days after delivery goods. If you have any problem with it, please leave a message to us. ♦Feedback●

Any comments, suggestions are accepted. We will be very grateful to your positive footprints left in our company. If you have any problem with our products, please leave a message to us.

♦Refund♦

Any damage or shortage of our goods after you receive your items, please take some photos for a witness. We will deal with it in 24 hours. Frequently, we will send a new part of items for heavy-damage. Before refund is accepted, please leave a message to us.

Skymen Technology Corporation Limited © 86-755-27094405 © info@skymen.cc © skymenultrasonic.com Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an
District, Shenzhen