

Rotisserie Basket Cleaning Service Soaking Tank Machine with 1.5KW Heating Power 168L


Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- · Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

Skymen

Shenzhen, China

- JP-168



- 1 Negotiation
 - Wooden case
- In Stock
- T/T
- 800 pcs per month



Product Specification

- Model:
- Tank Volume: • Heating Power:

JP-168L

- Internal Tank Size:
- Basket Size:
- Gross Weight:
- Highlight:
- 168L 1500W 655*410*625MM 605*390*595MM 120KG
- SUS316 Kitchen Soak Tank, 2mm Thickness Kitchen Soak Tank, FCC Heated Tank Cleaning Machine



More Images



Rotisserie Basket Cleaning Service Soaking Tank Machine with 1.5KW Heating Power 168L

Directions for use

Step



Fill the with (preferably hot) water to the 'Fill Line' marked on the inside, plug the tank into an electrical outlet, and switch ON






Slowly add the oil/Carbon-Removal Powder







the lid, leaving the items in the tank to soak, and walk away!





Remove the items from the tank, then simply rinse off any loose or softened carbon fragments.

PRODUCT SPECIFICATIONS

1	Model	JP-168					
	1st Tank	Function	Hot water cleaning/soaking				
		Tank Material	SUS 304 (SUS 316 can be customized)				
		Inner tank dimension	655*410*625mm				
		Tank Capacity	168L				
		Heating tube	1pcs				
		Heating Power	1500W				
2		Time setting	0~99 hours				
ŕ		Temperature setting	Room temperature ~ 80°C adjustable				
		Thickness of tank	2mm				
		Drain value	Yes, in the right side of machine				
		Water inlet/outlet	Yes				
		Lid	Yes, hinged with machine body, with gasket				
		Handle of the basket	Yes				
		Basket load	200KG				
	Packing	Overall size	755*510*785mm				
4			855*610*920cm				
		Packing detail	By wooden case(No logs, free of fumigation)				
5	Warranty		pare parts, all life technical support				
6	Certificate	CE, RoHS; FCC, RE	CE, RoHS; FCC, REACH				
7	Production time	5 days if there is stock; 20 days if there is no stock					

PRODUCT CONFIGURATION





Cleaning steps:

Fill in the tank with clean hot water to the max line; Add the detergent and stir the solution; Plug the machine into the electrical outlet and switch on; The solution will remains at 80°C; Load the cleaning items such as pots, pans, hood filters and more. Use the lifting basket to lower the items into the appliance. A light rinse is required before using items. Heavily carbonized equipment may need an additional soak. Close the lid, leaving the items in the tank to soak, and walk away. It will clean continuously, remove fat, grease, oil and carbon build up .

Suggest cleaning time:

Cleaning time		
Initial soak 12 hours		
Minimum of 12 hours		
Minimum 3~4 hours		
1 hour		
Initial soak 12 hours		
Minimum 12 hours		
Initial soak 12 hours		
1-2 hours		
Initial soak 12 hours		

Cleaning Effect show:

Korean BBQ Grill Plate Cleaner





Roasting Pan Cleaner

Sheet Pan Cleaner



Cake Pan Cleaner

Muffin Pan Cleaner



Rotisserie Basket Cleaner





Bakery shops; Hotel; Supermarkets; Schools, colleges, caterers; Food production facilities Small tank: for canopy fitlers, grill tops, pans and small trays; Medium tank(popular size): suitable for busy medium sized pans and large trays & oven racks; Large tank: suitable for greasy filters, pots, baking trays, etc; Skymen also offer custom sizes for larger applications. **Application Industrial:**

Restaurants;

Bakery shops;

Hotel; Supermarkets;

Supermarkets; Schools, colleges, caterers; Food production facilities Small tank: for canopy fitlers, grill tops, pans and small trays; Medium tank(popular size): suitable for busy medium sized pans and large trays & oven racks; Large tank: suitable for greasy filters, pots, baking trays, etc; Skymen also offer custom sizes for larger applications. Soaking tank with different capacity:

Soaking tank with different capacity:										
Model	Volume(L)	Internal tank size(MM)	Basket size(MM)	Unit size(MM)	Heating power	Material				
JP- 168	168L	655*410*625	605*390*595	755*510*785	1.5KW	SUS 304				
JP- 211	211L	750*450*625	700*430*595	850*550*785	1.5KW	SUS 304				
JP- 258	258L	890*480*605	840*460*575	990*580*800	3KW					
JP- 274	274L	840*480*680	790*460*650	940*580*875	3KW	SUS 304				
JP- 388	388L	1080*460*680	1060*440*650	1480*560*875	4.5KW	SUS 304				
JP- 483	483L	1365*520*680	1315*500*650	1465*620*875	6KW	SUS 304				

Factory and Warehouse







Skymen V Okymen Fechnology Corporation Limited
86-755-27094405 Sinfo@skymen.cc Bior 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen