

Skymen Ultrasonic Cleaner For Mouthpiece Of Vapor With Basket 200W Heater 1.72 Gallon

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Supply Ability:

1 unit	
Negotiation	
1unit per box	
In Stock	

8000 pcs per month

CE ROHS FCC SGS

China

Skymen

JP-031S

Product Specification

 Highlight: 	30min Timer Ultrasonic Parts Cleaners, Bench Top Ultrasonic Cleaner SUS304, SUS304 Ultrasonic Cleaning Equipment
• G.W:	6.6KG
Material:	SUS 304
 Heating Power: 	200W
 Ultrasonic Power: 	180W/90W
• Tank Size:	12*6*6 Inch
 Capacity: 	1.72 Gallon
 Frequency: 	40KHz
• Model:	JP-031S



More Images



Product Description

Nodel	<u>JP-031S</u>
JItrasonic Frequency	40KHz
ransducer Quantity	3pcs
Jltrasonic Power	180W/90W
leating Power	200W
ank Capacity	6.5L/1.75Gallon
ank Size	300*150*150mm
Aachine size	380*200*275mm
Packing size	410*255*360mm
let weight	6KG
Gross weight	6.6KG
Time Range	1~30 minutes
emperature Range	Room temperature~80°C/176°F
ank material	SUS 304
ank thickness	1mm
Shell thickness	0.8mm
Slope panel degree	20°
Drain Valve	✓ ✓
eneral switch	/
legas	1
Semi-wave	1
.id	/
Basket	1
/oltage	110V; 220V
Plug	European Plug; US plug; Austrslian Plug; British Plu
Detergent suggestion	No stronger acid or alkali
DEM	Yes
DEM MOQ	70pcs
Drigin	Guangdong China
Business category	Manufacturer
ead time	7 days after payment if order quantity is below 20pcs
Payment term	By cash; by credit card; by Paypal
Varranty	1 year

Heating Function to Remove Oil and Wax

Heating can decrease the adhesive strength of oil and wax to certain stuffs to be cleaned, make the cleaning solution much easiler to create cavitations under ultrasonic wave and strengthen cavitation so as to increase the cavitation level of cleaning solution, and then enhance the cleaning effect.

Note: the best cavitation temperature of water is 50~60 degrees celsius.

Stainless Bench Top




Model	Capacity	Tank Size	Ultrasonic Power	Heating Power	Frequency	Tank thickness	Material
	(L)	(L*W*H)mm	(W)	(W)	(KHz)	(mm)	SUS304
JP-008	0.8	150*85*65	35	0	40	1	SUS304
JP-009	0.9	150*135*65	60	100	40	1	SUS304
JP-010T	2	150*165*100	60	100	40	1	SUS304
JP-020S	3.2	240*135*100	120	100	40	1	SUS304
JP-030S	4.5	300*150*100	180	200	40	1	SUS304
JP-031S	6.5	300*150*150	180	200	40	1	SUS304
JP-040S	10	300*240*150	240	200	40	1	SUS304
JP-060S	15	330*300*150	360	300	40	1	SUS304
JP-080S	22	500*300*150	480	500	40	1	SUS304
JP-100S	30	500*300*200	600	500	40	1	SUS304
Product	Product Show:						









Fina warkmanakin and dorahilike



INDUSTRIAL SUS304 TANK

Thickness 1.1mm/Heat-resisting and corrosion-resisting/safe and healthy



One-stop throughout cleaning solution

With thermostat controls and heater; High frequency cleaning ; Intensive cleaning



SPECIAL FUNCTIONS



SKYMEN COORDINATOR

 Skymen Coordinator
 Other Coordinator

Application Area:

delivery a uniform and thorough cleaning performances.

APPLICATIONS

1 Scientific Labs

Eyeglass Frames, Lab Glassware, Optical & Contact Lenses, Pipettes, Scientific Instruments, Test Tubes...



2 Jewelry & Metal Decoration Manufacturing

Chains, Charms, Intricate Settings, Precious Metals, Gemstones, Coins, Watchbands...







3 Medical & Dental Lab

Burs, Blood Oxygenators, Cannulae, Dental Instruments, Syringe Parts, Surgical Instruments...



4 Industrial Manufacturing

Assemblies, Gears, Metal & Plastic Parts, Precision Bearings, Relays, Motors, Switches...



5 Electronics Manufacturing

Capacitors, Ceramic Substrates, PC Boards, Packaging Components, Quartz Crystals, SMDs...



6 Auto Industry

Carburetor, Castings, Fuel Injectors, Machined Parts, Stamped Parts, Switches...







Suitable for varieties of palces








Factory

Hardware store



MULTIPURPOSE CLEANING

It's efficient for most of household items that could be used to clean. get the best cleaning effects with the least effort.





COMPARISON OF CLEANING EFFECT



Industrial Ultrasonic Cleaning Machine



	Capacit	Tank Size	Transducer	Ultrasonic	Heating Power	Tank thicknose	Frequency	
Model	У	Talik Size	s	Power	nealing rower	Tarik (HICKHESS		
	(L)	(L*W*H)mm	(pcs)	(W)	(W)	(mm)	(KHz)	
JP-120ST	38	500X300X250	12	600	1500	2	28/40	
JP-180ST	53	500X350X300	18	900	1500	2	28/40	
JP-240ST	77	550X400X350	24	120	3000	2	28/40	
JP-300ST	99	550X450X400	30	1500	3000	2	28/40	
JP-301ST	99	800X300X400	30	1500	3000	2	28/40	
JP-360ST	135	600X500X450	36	1800	4500	2	28/40	
JP-480ST	175	700X500X500	48	2400 6000	6000	2	28/40	
JP-600ST	264	800X600X550	60	3000	6000	2	28/40	
JP-720ST	360	1000X600X600	72	3600	9000	2	28/40	
JP-	540	1000X900X600	108	5400	18000	2	28/40	
1108ST	0.10	1000/000/000	100	0100	10000	-	20/40	
JP-	960	1200X1000X800	144	7200	27000	2	28/40	
1144ST	190			. 200		-	20, 10	

Immersible Transducer Plate Image:



	Model	Plate Size	Transducer s	Ultrasonic Power	Generator	Suitable tank
		(L*W*H)mm	(pcs)	(W)	(set)	(L)
ſ	JP-1006I	305*205*100	6	300	1	10~15
ſ	JP-1012I	355*305*100	12	600	1	30~40
	JP-1018I	340*280*100	18	900	1	60~70
	JP-1024I	430*280*100	24	1200	1	70~80
	JP-1030I	460*370*100	30	1500	1	90~100
	JP-1036I	550*450*100	36	1800	1	130~140
	JP-1048I	600*450*100	48	2400	2	170~180

Immersible Transducer Tube Image:



	Tube Size Transduce Ultrasonic Powe	be Size	Generat	Length of wire		
Model		rs		or	Longar of Who	
	(D*H)mm	(pcs)	(W)	(set)	(M)	
JM-1003	57*180	3	150	1	1.5	
JM-1006	57*300	6	300	1	1.5	
JM-1012	57*550	12	600	1	1.5	
JM-1018	57*750	18	900	1	1.5	
JM-1024	57*1000	24	1200	1	1.5	
JM-1036	57*1520	36	1800	1		

Immersible Transducer Plate/tube can be put in any tank, but it doesn't have heating function.

The price of tube is much higher than plate, Ultrasonic Tube is only used for special purpose, such as in Lab.

Our Certificates:

CE, RoHS, FCC, REACH

QUALITY ASSURANCE

SKYMEN has passed more than 20 patents and international certifications, such as CE, ROHS, FCC, ISO13485, ISO9001, PSE.





