

20000L Ultrasonic Washing Machine 28KHz Cylindrical With Crane

Basic Information

Place of Origin: China
Brand Name: SKYMEN
Certification: CE, RoHs, FCC
Model Number: JP-11512ST

Minimum Order Quantity:

Price: Negotiation Packaging Details: wooden case Delivery Time: In Stock

• Supply Ability: 100 pcs per month



Product Specification

Cleaning Way: AutomaticChamber Dimension: 800*120*120cm

Frequency: 28KHz
Lift For Tower: Available
Tower Diameter: Below 1.6m
Heating Power: 72000W
Ultrasonic Power: 75600W
Crane: Available

• Highlight: 20000L Ultrasonic Washing Machine,

Ultrasonic Washing Machine 28KHz,

Cylindrical Ultrasonic Cleaning Equipments

Product Description

20000L Ultrasonic Washing Machine 28KHz Cylindrical Heat Exchanger with Crane Ultrasonic Cleaning Machine For Heat Exchanger

The traditional method of washing the heat exchanger is to use a high-pressure spray water gun. The cleaning cost is low, but there are also obvious disadvantages. If the water pressure is too large, the pipeline may be damaged, and the heat exchange tube cannot be cleaned inside, and there is still residual dirt. Ultrasonic cleaning equipment can solve this problem well. Using the cavitation of ultrasonic waves in water, the dirt attached to the surface of the heat exchange tube is loosened, peeled off in water, and the internal pipes and gaps are effectively cleaned.

The most suitable cleaning temperature for the water cleaning solution is 50-60 ° C. Especially in the case of cold weather, if the temperature of the cleaning solution is low, the cavitation effect is poor, and the cleaning effect is also poor. Therefore, some washing machines are wound around the heating cylinder to heat the heating wire for temperature control. When the temperature rises, cavitation is easy to occur, so the cleaning effect is good. When the temperature continues to rise, the gas pressure in the bubble increases, causing the impact sound pressure to drop, reflecting the multiplication of the two factors.

Detailed Specification of this machine:

| 1 | Model | UP-11512ST | |
|---|--------------|---|---|
| Ŀ | III.GGG! | Function | Ultrasonic cleaning |
| | | Ultrasonic Frequency | 28/40kHz (other frequency can be customized) |
| | | Tank Material | SUS 304 (SUS 316 can be customized) |
| | | Thickness of tank | 3mm |
| | | Inner tank dimension | 8000*1600*1600mm |
| | | Tank Capacity | 20480L |
| | | Transducer | 1512pcs |
| | | Ultrasonic Power | 75600W |
| | | Heating Power | 72000W |
| 2 | Parameter | Time setting of | 72000 |
| _ | | Ultrasonic | 0~99 hours |
| | | Temperature setting | Room temperature ~ 95°C adjustable |
| | | Drain value | Available |
| | | Water inlet/outlet | Available |
| | | Generator | 42 sets |
| | | Generator power control | 1800W |
| | | Generator shelf | Available |
| | | Basket | Available |
| | | Basket load | 8000KG |
| | | Overall size | 870*210*250cm |
| 3 | Packing | Packing size | 880*220*280cm |
| ۲ | racking | Packing detail | By wooden case(No logs, free of fumigation) |
| | | N.W/G.W | 9000KG/9500KG |
| 4 | Power supply | 380V 3 phase; 220V 3 pa | hse; 415V; 600V |
| 5 | Warranty | 1 year warranty for spare | parts, all life technical support |
| 6 | Certificate | CE, RoHS; FCC, REACH | İ |
| 7 | Lead time | 20~30 working days after | deposit |
| | | Filtration cycle system | Available; capture dirty water, recycle clean water |
| | | Lifting system for basket | Available; take the basket up and down |
| | | Dunking system | Available; Speed up cleaning |
| | | Bubbling | Available; need to connect air compressor |
| | | Electrolysis | Available; For cleaning more complex structure mold |
| 7 | Optional | Cooling system | Available; To cool down inflammable and explosive |
| | functions | Constant temperature | Available; |
| | | Roller barrel | Available; for clean coins and big quantity parts |
| | | Anti-explosion electric box | Available; |
| | | Crane | Available; |
| | | Deionized(DI) water | Available; |
| | | Double/Multi frequency | Available; 28/40/20/68/80/132KHz |
| | | Other funtions | Negotiate via email |
| | 1 | 1- : ::: :::::::::::::::::::::::::::::: | - 9 - : - 3-2 - 1-8 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - |



Other size and capacity for reference:

| Brand | Skymen | | | |
|---------------------|--|------------------|---------------------|--|
| Model | JP-1216ST | | | |
| Inner tank size | 1500*1000*1000mm | Capacity | 1500L | |
| Transducer | 216pcs | Ultrasonic power | 0~10800W Adjustable | |
| Frequency | 28/40KHz | Heating power | 36000W | |
| Max power | 46800W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen JP-1288ST | | | |
|---------------------|--|------------------|---------------------|--|
| Model | | | | |
| Inner tank size | 2000*1200*800mm | Capacity | 1920L | |
| Transducer | 288pcs | Ultrasonic power | 0~14400W Adjustable | |
| Frequency | 28/40KHz | Heating power | 45000W | |
| Max power | 59400W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen JP-1360ST | | | |
|---------------------|--|------------------|---------------------|--|
| Model | | | | |
| Inner tank size | 2000*1200*1000mm | Capacity | 2400L | |
| Transducer | 360pcs | Ultrasonic power | 0~18000W Adjustable | |
| Frequency | 28/40KHz | Heating power | 54000W | |
| Max power | 72000W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen JP-1432ST | | | |
|---------------------|--|------------------|---------------------|--|
| Model | | | | |
| Inner tank size | 2000*1500*1200mm | Capacity | 3000L | |
| Transducer | 432pcs | Ultrasonic power | 0~21600W Adjustable | |
| Frequency | 28/40KHz | Heating power | 63000W | |
| Max power | 84600W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen JP-1576ST | | | |
|---------------------|--|------------------|---------------------|--|
| Model | | | | |
| Inner tank size | 2500*1500*1200mm | Capacity | 4500L | |
| Transducer | 576pcs | Ultrasonic power | 0~28800W Adjustable | |
| Frequency | 28/40KHz | Heating power | 63000W | |
| Max power | 91800W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen | | | |
|---------------------|--|----------------------|---------------------|--|
| Model | JP-1648ST | | | |
| Inner tank size | 3000*1500*1200mm | Capacity | 5400L | |
| Transducer | 648pcs | Ultrasonic power | 0~32400W Adjustable | |
| Frequency | 28/40KHz | Heating power | 63000W | |
| Max power | 95400W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, t | echnical support alw | rays | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen | | | |
|---------------------|---|------------------|---------------------|--|
| Model | JP-1720ST | | | |
| Inner tank size | 4000*1600*1000mm | Capacity | 6400L | |
| Transducer | 720pcs | Ultrasonic power | 0~36000W Adjustable | |
| Frequency | 28/40KHz | Heating power | 66000W | |
| Max power | 102000W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Application | | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system Spraying, etc | | | |

| Brand | Skymen JP-1936ST | | | |
|---------------------|--|------------------|---------------------|--|
| Model | | | | |
| Inner tank size | 3500*1600*1300mm | Capacity | 7280L | |
| Transducer | 936pcs | Ultrasonic power | 0~46800W Adjustable | |
| Frequency | 28/40KHz | Heating power | 66000W | |
| Max power | 112800W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen JP-11152ST | | | |
|---------------------|--|------------------|---------------------|--|
| Model | | | | |
| Inner tank size | 2500*2000*1700mm | Capacity | 8500L | |
| Transducer | 1152pcs | Ultrasonic power | 0~57600W Adjustable | |
| Frequency | 28/40KHz | Heating power | 69000W | |
| Max power | 126600W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen JP-11224ST | | | |
|---------------------|---|------------------|---------------------|--|
| Model | | | | |
| Inner tank size | 3200*2000*1500mm | Capacity | 9600L | |
| Transducer | 1224pcs | Ultrasonic power | 0~61200W Adjustable | |
| Frequency | 28/40KHz | Heating power | 69000W | |
| Max power | 130200W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen JP-11368ST | | | |
|---------------------|--|------------------|---------------------|--|
| Model | | | | |
| Inner tank size | 8000*1200*1200mm | Capacity | 11520L | |
| Transducer | 1368pcs | Ultrasonic power | 0~68400W Adjustable | |
| Frequency | 28/40KHz | Heating power | 69000W | |
| Max power | 137400W | Power supply | 380V/220V 3 Phase | |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours | |
| Tank material | SUS 304 | Tank Thickness | 3mm | |
| Water inlet/outlet | Yes | Caster | Yes | |
| Basket | Yes | Manual | Available | |
| Warranty | 1 Year, technical support always | | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | | |

| Brand | Skymen | | |
|---------------------|--|------------------|---------------------|
| Model | JP-11512ST | | |
| Inner tank size | 8000*1600*1600mm | Capacity | 20480L |
| Transducer | 1512pcs | Ultrasonic power | 0~75600W Adjustable |
| Frequency | 28/40KHz | Heating power | 72000W |
| Max power | 147600W | Power supply | 380V/220V 3 Phase |
| Temperature control | Room temperature~95°C | Time control | 0~99 Hours |
| Tank material | SUS 304 | Tank Thickness | 3mm |
| Water inlet/outlet | Yes | Caster | Yes |
| Basket | Yes | Manual | Available |
| Warranty | 1 Year, technical support always | | |
| Application | Heat exchanger; Boiler; BBQ grills; Mold, Casting; etc. | | |
| Available functions | Water filtration system; Lifting system for basket; Bubble system; Spraying, etc | | |

Product show:















Cleaning effect show:

CLEANING EFFECT

Better cleaning when cleaning with detergent





Skymen Cleaning Equipment Shenzhen CO., Ltd.







The role of the Crane:

When you clean the items, it is more difficult to put the items in or out of the washing tank. The crane can solve this difficulty very well, just start the button, the object will automatically immerse and lift the sink, very labor-saving.



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen