



Precision Parts 1500W Ultrasonic Washing Machine Electrolysis Mold 95 Celsius

Our Product Introduction

for more products please visit us on skymenultrasonic.com

Basic Information

- Place of Origin: China
- Brand Name: SKYMEN
- Certification: CE, RoHs, FCC
- Model Number: JTS-1030
- Minimum Order Quantity: 1
- Price: Negotiation
- Packaging Details: wooden case
- Delivery Time: In Stock
- Supply Ability: 1000 pcs per month



Product Specification

- Feature: Electrolysis
- Cleaning Type: Immersion / Soak
- Power: 1500W+3000W
- Dimension(L*W*H): 550 X 450 X 400mm
- Application: Clean Precision Mold
- Temperature Setting: 95 Celsius / 203 Fahrenheit
- Ultrasonic Frequency: 28KHz/40KHz
- Transducer: 30pcs
- Highlight: Precision Parts Ultrasonic Washing Machine, 1500W Ultrasonic Washing Machine, 95 Celsius Heating Ultrasonic Cleaner



More Images



Product Description

Electrolysis Mold Ultrasonic washing machine for Precision Parts Heating ultrasonic cleaner

1. Inner tank dimension of this machine: 550*450*400mm (Length × width × deep)
2. The inner tank dimension can be changed/custom according to the size of your Melt blown mould length
3. 1500W stronger ultrasonic power; 3000W heating power

Features at a Glance

1. Fast and thoroughly cleaning
2. Saving labor; time; detergent
3. Clean cracks and blind holes for mould
4. No damage to the mold
5. Removing heavy dirt and fabric easily
6. Power can be adjustable
7. SUS 304/SUS 316 tank material
8. Liquid level switch can be added
9. Thermal insulation can be added
10. With water inlet/out let in suitable place
11. With stainless steel basket
12. Filtration cycle system is available
13. Lifting system for basket is available
14. Electrolysis is available
15. Double/Multi frequency is available
16. Cooling system is available
17. Deionized(DI) water is available

Product Parameters

Model Number	JTS-1030
Function	Electrolysis + Hot water cleaning
Ultrasonic Frequency	28/40kHz (other frequency can be customized 20KHz 68KHz, 80KHz, 132KHz)
Tank Material	SUS 304 (SUS 316 can be customized)
Thickness of tank	2mm
Inner tank dimension	550*450*400mm / 31*12*16 inch (Length*width*deep)
Machine dimension	1000*900*1000mm (Length*width*height)
Packing dimension	1100*1000*1200mm (Length*width*height)
Gross weight of machine	130KG
Tank Capacity	99 Liter / 26 Gallon
Transducer	30pcs; 50W for each transducer; 100W transducer can be customized
Ultrasonic Power	1500W
Heating Power	3000W
Time setting of Ultrasonic	0~99 hours
Temperature setting	Room temperature ~ 95°C / 203°F adjustable
Drain hole	On the bottom of inner tank
Water inlet/outlet	Yes; 20mm
Basket	Yes; ,
Basket load	More than 200KG
Length of power line	1.5 meters
Power supply	220V 50Hz; 110V 60Hz
Warranty	1 year
Certificate	CE; RoHS; FCC; REACH
Lead time	25 days after payment

Cleaning Effect

□

□

Similar models with different tank volume:

Model	Tank size	Volume	Ultrasonic Power	Heating Power	Transducer
	L*W*H (mm)	(L)	(W)	(W)	(pcs)
JP-120ST	500X300X250	38L	600W	1500W	12pcs
JP-180ST	500X350X300	53L	900W	1500W	18pcs
JP-240ST	550X400X350	77L	1200W	3000W	24pcs
JP-300ST	550X450X400	99L	1500W	4500W	30pcs
JP-301ST	800X300X400	96L	1500W	4500W	30pcs
JP-360ST	600X500X450	135L	1800W	4500W	36pcs
JP-480ST	700X500X500	175L	2400W	6000W	48pcs
JP-600ST	800X600X550	246L	3000W	6000W	60pcs
JP-720ST	1000X600X600	360L	3600W	9000W	72pcs
JP-1108ST	1000X900X600	540L	5400W	18000W	108pcs
JP-1144ST	1200X1000X800	960L	7200W	27000W	144pcs

□

□

□

-
-
-
-
-
-
-
-
-

Company Profile

Skymen Cleaning Equipment Shenzhen Co. Ltd., that has worked on ultrasonic cleaner for more than 13 years. Our ultrasonic products fully range from mini household ultrasonic cleaner, benchtop stainless steel small ultrasonic cleaner, and industrial large tank ultrasonic cleaner as well as Immersible ultrasonic transducer system. Our company devotes to research and development, with strong engineer teams. Otherwise, we accept customer's idea and want to develop new products together.

-

Ultrasonic cleaning of metal

It is well known that after the metal bar is extruded into a wire, the outer part of the wire often has a layer of carbonized film and oil. It is difficult to remove the dirt (especially the whole wire) by acid cleaning or other cleaning methods. The ultrasonic wire washing machine is According to the actual production needs, a continuous wire-cutting and high-efficiency cleaning equipment is used. The rough washing part is composed of a cleaning liquid storage tank, a transducer, a circulation pump, a filter and a matching piping system. After the wire is ultrasonically washed and washed, And then blow dry to complete the entire cleaning process. The integrated control of the whole set of equipment is simple, convenient and effective. It is widely used in other wires such as silk, tungsten wire, molybdenum wire, silk wire and copper wire (before the coating of insulating paint).



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen