

## Sus304 Touch Key 180W Digital Ultrasonic Cleaner 6.5l Heated

#### **Basic Information**

• Place of Origin: China (Mainland)

Brand Name: Skymen
Certification: CE RoHS
Model Number: JP-031S
Minimum Order Quantity: 1pcs
Price: Negotiation

• Packaging Details: 1pcs / carton (42\*28\*36cm)

• Delivery Time: In Stock

Payment Terms: Paypal, , Western Union, L/C, T/T

• Supply Ability: 3000pcs per month



### **Product Specification**

Material: Sus 304Brand: Skymen

• Tank Size: 300 X 150 X 150 Mm

Tank Capacity: 6.5LUltrasonic Power: 180wHeating Power: 200W

• Timer: 1-30min Adjust

• Certification: CE, RoHS, ISO9001:2008

Transducer: 3pcsFrequency: 40KHZHeater: 20-80C

• Highlight: Sus304 Touch Key Digital Ultrasonic Cleaner,

180W Digital Ultrasonic Cleaner, 6.5I Heated Ultrasonic Parts Cleaner

# Sus 304 Touch Key 6.5l Table Top Ultrasonic Cleaner For Spare Parts Cleaning

More thorough cleaning- cleans down to one micron cleanliness level
Shorter cleaning times- 3-5 minutes for most firearms
Less handling- allows the user to perform other functions while cleaning is in process
Lubrication tank design uses ultrasonic energy allowing complete coverage in every crack and crevasse
Cleaning detergent is specifically chosen for firearm cleaning and includes a rust prohibitor
Lubrication is specially formulated for firearm cleaning with water displacement and low temperature properties

#### **Product description:**

Skymen 6.5L digital ultrasonic cleanr JP-031S
With digital timer & heater
Having great cleaning and sterilizing effect with high frequency
Making the object like a new one
Saving time & labor
1 year warranty
Certificates: CE & RoHS

#### Specifications:

Ultrasonic frequency	40,000 Hz			
Material	Stainless Steel SUS304			
Tank Capacity	6.5 L			
Timer	1-30minutes, digital timer			
Power Supply	AC 100 ~ 120V, 50 / 60Hz			
г ожег оарргу	AC 220 ~ 240V, 50 / 60 Hz			
Ultrasonic Power	180W			
Heating Power	150W, digital heating			
Unit Size	325 x 180 x 280 mm (LxWxH)			
Tank Size	300 x 150 x 150 mm ( L x W x H )			
Package Size	450 x 300 x 380 mm (LxWxH)			
N.W.	5.6 kg			
G.W.	6.6 kg			

#### Features:

- 1. Stainless steel tank has resistance to wear and long work life.
- 2. Tank capacity:6.5L, with timer & heater control
- 3. With Stainless steel basket
- 4. Use tab water, or industrial alcohol and solvent cleaner for more higher cleaning requirement
- 5. Industrial control chip microcontroller flexible circuit boards control, more secure & stable
- 6. Temperature tunable from 20°C to 80°C
- 7. Certification:CE&RoHS

#### Other models for your choice:

#### Commercial ultrasonic cleaner with handle, no casters:

00	Commercial ditrasome cicaner with namice, no casters.								
		Unit size	Volu me		Ultrasonic frequency	Heating power		Heating temperature	
	L×W×H(m m)	m) `	(L)	Normal (W)	(kHz)	(W)	(MI N)	(°C)	
JP- 010T	150×135× 100	175×160× 210	2	60		100	1- 30	0-80	
JP- 020T	100	265×165× 220	3.2	120/60		100	1- 30	0-80	
JP- 030T	100	325×180× 225	4.5	180/90		200	1- 30	0-80	
JP- 031T	150	325×180× 280	6.5	180/90		200	1- 30	0-80	
JP- 040T	150	325×265× 280	10.8	240/120	40	200	1- 30	0-80	
0501	00	325x265x3 30	14.5	300/150		200	1- 30	0-80	
JP- 060T	150	360×325× 285	15	360/180		300	1- 30	0-80	
JP- 070T	00	35	20	480/240		300	1- 30	0-80	
JP- 080T	150	530×325× 285	22	480/240		500	1- 30	0-80	
JP- 100T	500×300× 200	530×325×3 25	30	600/300		500	1- 30	0-80	

#### Industrial ultrasonic cleaner with casters and brake:

Model	Tank size	Volum e	Ultrasonic power		power	r	Heating temperature
	L×W×H(mm)	(L)	Normal (W)	(kHz)	(W)	(MIN )	(°C)
120ST	500x 300x 250	38	240-600		1500		
18051	500x350x300	53	360-900		3000	1_00 (	20-80
2405 I	550x400x350	77	480-1200		3000		
30051	550x450x400	99	1500	28/40	4500		
36051	600x500x450	135	1800		4500	1 33	20 00
4805 I	700x500x500	175	2400		6000		
100051	800x600x500	l -	3000		6000		
JP- 720ST	1000×600×60 0	360	3600		9000		

#### Features:

- 1. stainless steel tank has resistance to wear and long work life.
- 2. tank capacity: 6.5L
- 3. with digital timer & heater control
- 4. with degas function to prevent oxidation
- 5. With double ultrasonic power
- 6. with Stainless steel basket
- 7. Use just tab water, or industrial alcohol and solvent cleaner for more higher cleaning requirement
- 8. industrial control chip microcontroller.flexible circuit boards control, more secure & stable
- 9. temperature tunable from 20°C to 80°C
- 10. timer 0-30min adjustable
- 11. certification:CE & RoHS

#### **Applications:**

Jewelry industry, medical industry, electronic factory, molding factory, car workshop, diesel workshop, car industry, scientific laboratory, university, dental clinics, eyeglass shop, hardware tools shop.

ULTRASONIC CLEANING involves the use of high-frequency sound waves (above the upper range of human hearing, or about 18 kHz) to remove a variety of contaminants from parts immersed in aqueous media. The contaminants can be dirt, oil, grease, buffing/polishing compounds, and mold release agents, just to name a few. Materials that can be cleaned include metals, glass, ceramics, and so on. Ultrasonic agitation can be used with a variety of cleaning agents: detailed information about these agents is available in the other articles on surface cleaning in this Section of the Handbook.

#### **Detail pictures:**



Packing info: 1 pcs / carton (42\*28\*36cm) Measurement for 1pcs:0.052CBM 18pcs per CBM



#### **Skymen Technology Corporation Limited**



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen