

China

Skymen

JP-031S

Negotiation

1unit per box

8000 pcs per month

In Stock

CE ROHS FCC SGS

# SUS304 Tank 6.5L 180W Medical Ultrasonic Cleaner For Fuel Injector

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 unit
- Price:
- Packaging Details:
- Delivery Time:
- Supply Ability:



# Product Specification

<ul> <li>Model:</li> </ul>	JP-031S
Capacity:	6.5L
• Tank Size:	300*150*150mm
Unit Size:	375*200*275mm
<ul> <li>Paking Size:</li> </ul>	350*260*350mm
Ultrasonic Power:	90W/180W
• Timer:	0-30 Minutes Adjustable
• Frequency:	40KHz
• Material:	SUS 304
• G.W:	6.2KG
<ul> <li>Power Supply:</li> </ul>	AC 110V ; AC 220V
<ul> <li>Heating Power:</li> </ul>	200W
• Highlight:	SUS304 Tank Medical Ultrasonic Cleaner, 180W Medical Ultrasonic Cleaner, 6.5L Skymen Ultrasonic Cleaner

### **Product Description**

### Lab Medical Ultrasonic Cleaner 6.5L 180W High Frequency Ultrasonic Cleaner SUS304 tank

Features: Sensitive touch control panel Digital Control display More convenient for operation Stainless steel tank has resistance to wear and long work life. Tank capacity: 6.5L Digital timer, clear digital LCD display With Stainless steel basket Use just tab water, or industrial solvent cleaner for more higher cleaning requirement Industrial control chip microcontroller.flexible circuit boards control, more secure & stable JP-031S product specification: Ultrasonic 40,000Hz frequency Material of tank SUS304 Material of shell SUS304 Capacity 6.5L Timer Digital control, 0~30 mins 200W Heater Power supply type AC 100~120V, 50/60Hz Power supply type AC 220~240V, 50/60Hz Ultrasonic power 90W /180W Tank inner 300\*150\*150mm dimension Unit dimension 375\*200\*275mm Inner Packing size 350\*260\*350mm Transducer 3pcs N.W. 5.4kg G.W. 6.2kg SGS & CE & RoHS & Certificate

# How to Use an Ultrasonic Cleaner for Medical & Surgical Instruments

Medical and surgical instruments in a variety of sizes and complexity can pose challenges when it comes to cleaning, disinfecting and sterilizing them after use. An ultrasonic cleaner is an ideal tool for the first step in this three step process to protect medical personnel and patients from possible infection due to pathogens that remain on the instruments after a procedure.

### Suggested Ultrasonic Cleaning Procedure

FCC

In all cases manufacturers' instructions should be followed when using an ultrasonic cleaning process. These are representative steps.

Fill the ultrasonic cleaning tank with an approved medical instrument cleaning solution such as CLN-LR012 available from Tovatech following dilution instructions provided. Turn the cleaner on to start the degassing process. This step removes entrained air in new solutions that interferes with the efficiency of cavitation and takes approximately 10 minutes. In the meantime:

Segregate instruments by alloy or composition to avoid potential damage (Chromium plated instruments should not be cleaned ultrasonically)

Instruments with movable parts should be disassembled to facilitate cleaning

Place the instruments the ultrasonic cleaner's mesh basket, taking care that they do not come in contact with each other Cannulated or lumened instruments should be positioned to insure interiors are wetted with the cleaning solution. In some instances placing them on an angle will facilitate this

Set the control panel per manufacturers' instructions and start the cleaning process

At the end of the cycle, remove the instruments from the ultrasonic cleaning bath and thoroughly rinse them to remove all traces of the cleaning solution. Deionized water rinses will avoid spotting. If the instruments are not to be immediately disinfected and sterilized be certain that they are thoroughly dried and protected. Part reassembly can occur after sterilization. Procedures should be in place to guide the replacement of used ultrasonic cleaning solutions. In some instances it is recommended that solution be drained and tanks thoroughly cleaned and dried after each ultrasonic cleaning cycle. Most solutions available today are biodegradable, which facilitates disposal but local authorities should be consulted on proper practices.

The ultrasonic cleaner uses ultrasonic waves (vibration) using water with detergents or enzymatic products to break up soil and organic material on medical instruments/devices. These devices are rinsed then autoclaved (sterilized). The autoclave sterilizer uses heat, steam, and pressure to kill all pathogenic microorganisms and their spores.

Control panel:


for more products please visit us on skymenultrasonic.com



products details:

# **PRODUCT DETAIL**

SKYMEN specialize in ultrasonic cleaners manufacturing since 2007, Professional team, quality assurance



# 1

**Cooling vents** 

Quickly cool the internal components of the machine, protecting the circuit board.



Insulation handle design, anti-static, anti-high temperature, not slippery hand, more secure.






Λ



Independent switch operation safety, built-in spare fuse, double insurance.





### Application:

Jewelry industry, medical industry, electronic factory, molding factory, car workshop, diesel workshop, car industry, scientific laboratory, university, dental clinics, eyeglass shop, hardware tools shop, printing industry.

# MULTIPURPOSE CLEANING

It's used in various industries from automotive to electronics to medical facilities for a number of applications.



Working priciple of Ultrasonic Cleaner

## DIRT ELIMINATION PROCESS THROUGH ULTRASONIC TECHNOLOGY


# Cleaning effect will be much better if using the machine together with proper solvent.



As ultrasonic wave through the solution in the tank, cause alternating high and low pressures in the solution.

Package Includes: 1 x Digital Ultrasonic Cleaner 1 x Cleaning Basket 1 x Manual






During the low pressure stage, millions of microscopic bubbles form and grow. This process is called "CAVITATION". During the high pressure stage, the bubbles implode releasing enormous amounts of energy. They work in all directions, attacking surface and invading all recesses and openings.

# <section-header>

**Cleaning effect:** 

# **CLEANING EFFECT**

Better cleaning when cleaning with detergent



Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen