

Shenzhen, China

RoHS, CE, FCC, SGS

Skymen

1

JTM-3216AD

Negotiation Wooden case

800 pcs per month

In Stock

Automated

5400W*2

18000W

39*35*24 Inch

143 Gallon

FCC SUS304 5400W Ultrasonic Cleaning Machine 143 Gallon With Hot Air Dryer

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T
- Supply Ability:



Product Specification

- Working Way:
- Functions:
- Ultrasonic Power:
- Heating Power:
- Single Stage Size:
- Single Stage Volume:
- Highlight:
- FCC SUS304 Ultrasonic Cleaning Machine, 5400W Ultrasonic Cleaning Machine, 143 Gallon Ultrasonic Parts Cleaners

Cleaning, heating, Cooling; Drying, Etc

Our Product Introduction

Product Description

Automatic Ultrasonic Cleaner for Precision Electronic Parts With Hot Air Dryer

I intended to replace all the ball bearings in my 50+ year old Hendey Tool & Gage lathe. After purchasing a few replacements, I though it might be more practical to clean and then inspect the old ones. Only those in bad shape would be replaced. I have a small ultrasonic cleaner and it has worked wonders on small items. If an ultrasonic cleaner is used, do the individual balls vibrate against the cage and inner race causing microscopic pitting on the surface of the balls which ruins the bearing? This concern came about due to the warnings about not spinning dry bearings (after cleaning but before application of grease or oil). What would be a easily obtainable solvent for removing the old grease? I don't want to use anything containing methylene chloride.

Specification sheet:

4	ecification sh						
1	Model	JTM-3216AD					
	1	Function	Ultrasonic cleaning + Filter+ Hot water cleaning				
	1st Chamber	Ultrasonic Frequency	28/40kHz (other frequency can be customized)				
		Tank Material	SUS304 (SUS 316 can be customized)				
		Thickness of tank	2mm				
		Inner tank dimension	39*35*24 inch				
		Tank Capacity	143 Gallon				
2		Transducer	60pcs				
		Ultrasonic Power	3000W				
		Heating Power	6000W				
		Time setting of	0~99 hours				
		Ultrasonic					
		Temperature setting	Room temperature ~ 95°C adjustable				
		Drain value	Yes				
		Water inlet/outlet	Yes				
		Filter	1 set, connect with 1st tank				
		Filtet element precision	5/10µ				
		Generator	2pcs				
		Generator power control	1500W				
		Basket	Yes				
		Basket load	200KG				
			Ultrasonic cleaning + Bubbling + Hot water				
	2nd Chamber	Function	cleaning				
		Ultrasonic Frequency	28/40kHz (other frequency can be customized)				
		Tank Material	SUS 304 (SUS 316 can be customized)				
		Thickness of tank	2mm				
		Inner tank dimension	39*35*24 inch				
		Tank Capacity	143 Gallon				
		Transducer	60pcs				
		Ultrasonic Power	3000W				
		Heating Power	6000W				
3		Time setting of					
		Ultrasonic	0~99 hours				
		Temperature setting	I Room temperature ~ 95°C adjustable				
		Drain value	Yes				
		Water inlet/outlet					
			Yes				
		Bubbling system	Yes, air compressor is provided by user				
		Generator	2pcs				
		·	1500W				
		Basket	Yes				
		Basket load	200KG				
	3rd Chamber	Function	Hot air drying tank				
3		Inner tank dimension	39*35*24 inch				
•		l urbines power	750W				
		Dryer power	3000W				
	Working way of machine	Working way	Full automatic				
		Loading and unloding	Yes				
4		platform					
		Moving way of basket	By mechanical arm				
		Control way	PLC touch screen				
5	Warranty	1 year warranty for spare parts, all life technical support					
6	Certificate	CE, RoHS; FCC, REACH					
_	Production						
		35 working days after deposit					

Working way

The entire process of putting the basket into the cleaning tank, removing the basket and moving the basket between the tanks is automatically completed by a single-arm manipulator. This ultrasonic cleaning machine has a total of 3 working tanks, plus 1 loading and unloading station, a total of 4 stations.

Same series with different size for your choice:

Model	Size of every tank	Tank Volume	Ultrasoni c Power	Heating Power of Ultrasonic tank	Heating Power of drying tank	Transducer
	L*W*H (mm)	(L)	(W)	(W)	750W	(pcs)
JTM-3024AD	500X300X2 50	38L*3	600W	1500W*2	750W	24pcs
JTM-3036AD	500X350X3 00	53L*3	900W	1500W*2	750W	36pcs
JTM-3048AD	550X400X3 50	77L*3	1200W	3000W*2	750W	48pcs
JTM-3060AD	550X450X4 00	99L*3	1500W	3000W*2	750W	60pcs
JTM-3072AD	600X500X4 50	135L*3	1800W	4500W*2	750W	72pcs
JTM-3096AD	700X500X5 00	175L*3	2400W	6000W*2	750W	96pcs
JTM-3120AD	800X600X5 50	264L*3	3000W	6000W*2	750W	120pcs
JTM-3144AD	1000X600X 600	360L*3	3600W	9000W*2	750W	144pcs
JTM-3216AD	1000X900X 600	540L*3	5400W	18000W*2	1100W	216pcs
JTM-3288AD	12000*1000 *800	960L*3	7200W	24000W*2	1500W	288pcs

Images:



Clean effect:



