

960L Dpf Three Tank Industrial Ultrasonic Cleaner Baths SUS316 SkyMen JP-3288GH

Our Product Introduction

for more products please visit us on skymenultrasonic.com

Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: SkyMen
- Certification: RoHS, CE, FCC, SGS
- Model Number: JP-3288GH
- Minimum Order Quantity: 1
- Price: Negotiation
- Packaging Details: Wooden case
- Delivery Time: In Stock
- Payment Terms: T/T
- Supply Ability: 800 pcs per month



Product Specification

- Model: JP-3288GH
- Tank Volume: 960L
- Ultrasonic Power: 7200W*2
- Heating Power: 27000W*2
- Frequency: 40KHz/28KHz Optional
- Internal Tank Size: 1200*1000*800mm (L*W*H)
- Material: SUS316 304
- Condition: New
- Highlight: **Three Tank Industrial Ultrasonic Cleaner,
960L Dpf Industrial Ultrasonic Cleaner,
SUS316 Tank Ultrasonic Cleaner Baths**



Product Description

Skymen JP-3288GH 960L Dpf Three Tank Industrial Ultrasonic Cleaner Baths Cleaning

PRODUCT SPECIFICATIONS

No		
1	Model	JP-3288GH (Ultrasonic Cleaning + Filter+ Rising+ Hot Air Drying)
2	1st Tank	Function
		Ultrasonic Cleaning + Filter
		Ultrasonic Frequency
		28/40kHz (other frequency can be customized)
		Tank Material
		SUS 304 (SUS316 can be customized)
		Inner tank dimension
		1200*1000*800mm
		Tank Capacity
		960L
		Transducer
		96 pcs
		Ultrasonic Power
		7200W
		Heating Power
		27000W
		Time setting of Ultrasonic
		0~99 hours
		Temperature setting
		Room temperature ~ 95°C adjustable
		Thickness of tank
		1mm
		Drain value
		Yes, in the right side of machine
		Water inlet/outlet
		Yes
		Filter
		1 set, connect with 1st tank
		Generator
		1 set
		Lid
		Yes, hinged with machine body, with gasket
		Basket load
		200KG
3	2nd tank	Function
		Ultrasonic Cleaning + Rising
		Inner tank dimension
		1200*1000*800mm
4	3rd tank	Ultrasonic Power
		7200W
		Heating Power
		27000W
4	3rd tank	Function
		Hot Air Drying
		Inner tank dimension
		1000*600*600mm
		Dryer Power
		12000W
5	Warranty	1 year warranty for spare parts, all life technical support
6	Certificate	CE, RoHS; FCC, REACH
7	Production time	5 days if there is stock; 20 days if there is no stock

SIMILAR PRODUCTS

Model	Tank size (mm)	Capacity (L)	Transducer (pcs)	Ultrasonic power (W)	Heating power (W)	Frequency (kHz)	Generator (set)
JP-3024GH	500*300*250	38	24	600*2	1500*2	28/40	1
JP-3036GH	500*350*300	53	36	900*2	1500*2	28/40	1
JP-3048GH	550*400*350	77	48	1200*2	3000*2	28/40	1
JP-3060GH	550*450*400	99	60	1500*2	4500*2	28/40	1
JP-3072GH	600*500*450	135	72	1800*2	4500*2	28/40	1
JP-3096GH	700*500*500	175	96	2400*2	6000*2	28/40	2
JP-3120GH	800*600*550	264	120	3000*2	6000*2	28/40	2
JP-3144GH	1000*600*600	360	144	3600*2	9000*2	28/40	2
JP-3216GH	1000*900*600	540	216	5400*2	18000*2	28/40	3
JP-3288GH	1200*1000*800	960	288	7200*2	24000*2	28/40	4

Ultrasonic Cleaner's Specification

Details Specification

Model	Tank Size(mm)	Capacity	Timer	Frequency	Transducer pcs	Ultrasonic Power	Heating Power	Filtration	Drying Power	Drying Temperature
JP-3024GH	500X300X250	38L	1-99h	40/28KHz	24	600W*2	1.5KW*2	YES	3000W	20-150°C
JP-3036GH	500X350X300	53L	1-99h	40/28KHz	36	900W*2	1.5KW*2	YES	3000W	20-150°C
JP-3048GH	550X400X350	77L	1-99h	40/28KHz	48	1200W*2	3KW*2	YES	3000W	20-150°C
JP-3060GH	550X450X400	99L	1-99h	40/28KHz	60	1500W*2	3KW*2	YES	4500W	20-150°C
JP-3061GH	800X300X400	96L	1-99h	40/28KHz	30	1500W*2	3KW*2	YES	4500W	20-150°C
JP-3072GH	600X500X450	135L	1-99h	40/28KHz	72	1800W*2	4.5KW*2	YES	4500W	20-150°C
JP-3096GH	700X500X500	175L	1-99h	40/28KHz	96	2400W*2	6KW*2	YES	6000W	20-150°C
JP-3120GH	800X600X550	264L	1-99h	40/28KHz	120	3000W*2	6KW*2	YES	6000W	20-150°C
JP-3144GH	1000*600*600	360L	1-99h	40/28KHz	144	3600W*2	9KW*2	YES	6000W	20-150°C
JP-3168GH	1500X700X400	420L	1-99h	40/28KHz	168	4200W*2	15KW*2	YES	6000W	20-150°C
JP-3192GH	1200X500X800	480L	1-99h	40/28KHz	192	4800W*2	15KW*2	YES	9000W	20-150°C
JP-3216GH	1000X900X600	540L	1-99h	40/28KHz	216	5400W*2	18KW*2	YES	9000W	20-150°C
JP-3240GH	1000X800X800	640L	1-99h	40/28KHz	240	6000W*2	18KW*2	YES	9000W	20-150°C
JP-3264GH	1000X1000X800	800L	1-99h	40/28KHz	264	6600W*2	24KW*2	YES	12000W	20-150°C
JP-3288GH	1200X1000X800	960L	1-99h	40/28KHz	288	7200W*2	30KW*2	YES	12000W	20-150°C
JP-3432GH	1500X1000X1000	1500L	1-99h	40/28KHz	432	10800W*2	36KW*2	YES	18000W	20-150°C

Application Industry

Applied To Hardware,Electronic,Auto Parts,Optical,Semiconductor
New Energy, Aeronautics And AstronauticsRail Traffic
Petrochemical, etc



Hardware




The Electronics Industry



Auto Parts



Optical Industry



Semiconductor Industry



New Energy



Aeronautics And
Astronautics



Rail Transportation



Petrochemical Industry

The Reason For Choosing Us

U L T R A S O N I C C L E A N E R



Skymen Brand Ultrasonic Cleaner
Button Panel, Concise and Saving
Effort

VS



Other Brand, Inconvenient Operation



Skymen Brand Concave cylinder
Mouth design, No Overflowing Water
good noise elimination

VS



Other brand cleaning machine flat
cylinder mouth, water is easy to
splash out



Skymen brand using self-developed
ultrasonic generator, digital
automatic frequency scanning
stable output

VS



Other Brands, Using older
mechanical generators

Cleaning Comparison Example

No contrast, no harm



Operating principle:

The principle of an ultrasonic cleaner is to convert the acoustic energy of a power ultrasonic frequency source into mechanical vibration via a converter and irradiate the cleaning liquid in the tank with ultrasonic waves through the wall of the cleaning tank. The radiation of ultrasonic waves allows the microbubbles in the liquid in the tank to continue to vibrate under the action of the sound waves. It destroys dirt and adsorption on the surface of the cleaning part, eliminates fatigue damage of the dirt layer, and rubs the solid surface with the vibration of bubbles.



Skymen Technology Corporation Limited

☎ 86-755-27094405

✉ info@skymen.cc

🌐 skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen