

Skymen 1200W Submersible Ultrasonic Generator SUS304 With Sweep Mode

packing by box or wooden case; the packing

size decides by the machine

600 sets per month

Western Union, L/C, T/T, Paypal

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 set
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

	SUS304 Submersible Ultrasonic Generator, Sweep Mode Submersible Transducer Box
 Highlight: 	1200W Submersible Ultrasonic Generator,
• Feature:	Hard Cr+ Plating
Custom Made:	Transducer Box Size
 Frequency: 	22kHz
• Warranty:	1 Year
• Material:	SUS304
• Model:	JTM-1018

China

CE

Skymen

JTM-1018

Negotiation

In Stock

Our Product Introduction

Skymen 1200W Ultrasonic Generator With Sweep Mode Submersible Transducer Box

Ultrasonic technology extraction is beyond any previous technical feasibility, access to efficient extraction, more effective than heat extraction resident agency regulations, and shortens the extraction time, most of the material before the process is to be extracted within 10min.

Packing & delivery details:

Packing , loading, delivery time				
Packing unit	1set/wooden case			
Packing method	Export wooden case			
Loading port	Shenzhen			
Delivery time	About 15 working days			
Minimum Order Quantity	1set			
Transport method	By express company / air / sea			

Transducer pack Specifications:

Model (JTM models)		JTM- 1006	JTM- 1012	ЈТМ	-1018	JTM- 1024	JTМ- 1030	JTM-1036	
Ultrasonic		305	355 406			500	550 500)
transducer box	W	250	305 305			355	406 460)
size (mm)	н	100	100	100		100	100	100	
Housing material	SUS304/SUS316L								
Surface finishing Ha		Hard-Cr plating treatment (20+microns)							
Ultrasonic frequency	28KHz / 40KHz								
Ultrasonic transducers	6рс	s	12pcs	-	8pcs	24pcs	30pcs		36pcs
Ultrasonic power	300	W	600W		900W	1200W	1500W		1800W
Electronic		300	KG600		<g900< td=""><td>KG1200</td><td colspan="2">KG1500</td><td>KG1800</td></g900<>	KG1200	KG1500		KG1800
generator	Ultrasonic generator work separately control transducers								
power suppy AC 1		C 110V/220V or 220/240V, 1,13AMP							
*Custom made:68	KH	z/80KHz/1	20KHz and	d size	are all a	available			

Features:

Original BLT type transducer

SUS stainless steel housing Hard-Cr plating Treatment (20 + microns)

Adaptable for continuous operation

Adjustable ultrasonic power

With separate control ultrasonic electronic generator

Custom made size is available

Transducer no./transducer box: range[6pcs~40pcs per box]

Ultrasonic power: range[300W~2000W]

Ultrasonic frequency: 28KHZ/40KHz

underwater ultrasonic transducer generator Features:

Original BLT type transducer

SUS stainless steel housing Hard-Cr plating Treatment (20 + microns)

Adaptable for continuous operation

ultrasonic generator with sweep mode

User-friendly operation

Transducer no./transducer box: range[6pcs~36pcs per box]-transducer box size can be custom made

Ultrasonic power: range[300W~1800W]

Ultrasonic frequency: 28KHZ/40KHz

Cleaning feature

1.Submersible Transducers are manufactured to meet individual customer specifications, ensuring the size and ultrasonic power are tailored to provide the cleaning and processing results.

2. These submersible transducers provide excellent ultrasonic activity and are easily controlled through Ultrawave's technologically advanced Convenience Install

Submersible Transducers can be easily installed or retro-fitted to an existing tank, allowing easy service and maintenance whilst having the benefits of an upgraded system with ultrasonic cleaning technology.

ultrasonic transducer generator hose tube



SKYMEN CLEANING EQUIPMENT SHENZHEN CO., LTD



Marketing Center 3rd Floor, Building A1, Fuhai Information Port, Fuyong Street, Baoan District, Shenzhen, Guangdong Province



Production base Wujiang Science and Technology Park (Skymen Industrial Park), Wujiang District, Shaoguan City, Guangdong Province



R&D Center No.10, Jian'an Road, Bao'an District, Shenzhen, Guangdong Province (Taifeng Industrial Zone)

• SKYMEN •



Customer Success Cases

Centralized Control Simple Operation Adjustable Power

Stable Performance





Application Industry

Applied in electromechanical, painting, aerospace, electroplating, automotive, electronics industry, prevent printing, new energy, petrochemical industry, etc.



Why Choose Us?



Reduce the number of solder joints, and the water leakage performance is better!



Industrial Transducer

✔ Strong work ✔ Stable output

Low heat generation
Long service life



Strong & Consistent Quality

The transducer is like the heart of a ultrasonic cleaner, the brand of Skymen industrial transducer



Skymen independent research and development focus on quality

Ultrasonic power can be adjusted and the workpiece is adaptable, and the cleaning efficiency is high, Ultrasonic strength is strong and uniform, and the performance is stable



Powerful ultrasonic power
 High quality material
 Brilliant workmanship









[Transducer Box Parameter]

Model	Inner tank size /volume	Time control	Frequency (optional)	Transducer pcs	Adjustable power	Material (optional)
JP-1006I	305*205*100mm	1-99min	28/40KHz	6	0-300W	304/ 316/ Titanium alloy
JP-1012I	355*305*100mm	1-99min	28/40KHz	12	0-600W	
JP-1018I	340*280*100mm	1-99min	28/40KHz	18	0-900W	
JP-1024I	430*280*100mm	1-99min	28/40KHz	24	0-1200W	
JP-1030I	460*370*100mm	1-99min	28/40KHz	30	0-1500W	
JP-1036I	550*450*100mm	1-99min	28/40KHz	36	0-1800W	
JP-1048I	600*450*100mm	1-99min	28/40KHz	48	0-2400W	

Size, installation method and outlet location can be customized according to requirements

Products Real Shot













How to Use an Ultrasonic Cleaner for Medical & Surgical Instruments

Medical and surgical instruments in a variety of sizes and complexity can pose challenges when it comes to cleaning, disinfecting and

sterilizing them after use. An ultrasonic cleaner is an ideal tool for the first step in this three step process to protect medical

personnel and patients from possible infection due to pathogens that remain on the instruments after a procedure.

Suggested Ultrasonic Cleaning Procedure

In all cases manufacturers' instructions should be followed when using an ultrasonic cleaning process. These are representative steps.

Fill the ultrasonic cleaning tank with an approved medical instrument cleaning solution such as CLN-LR012 available from Tovatech following dilution instructions provided. Turn the cleaner on to start the degassing process. This step removes entrained air in new solutions that interferes with the efficiency of cavitation and takes approximately 10 minutes. In the meantime:

Segregate instruments by alloy or composition to avoid potential damage (Chromium plated instruments should not be cleaned

ultrasonically)

Instruments with movable parts should be disassembled to facilitate cleaning Place the instruments the ultrasonic cleaner's mesh basket, taking care that they do not come in contact with each other Cannulated or lumened instruments should be positioned to insure interiors are wetted with the cleaning solution. In some instances placing them on an angle will facilitate this

Set the control panel per manufacturers' instructions and start the cleaning process

At the end of the cycle, remove the instruments from the ultrasonic cleaning bath and thoroughly rinse them to remove all traces of the cleaning solution. Deionized water rinses will avoid spotting. If the instruments are not to be immediately disinfected and sterilized be certain that they are thoroughly dried and protected. Part reassembly can occur after sterilization. Procedures should be in place to guide the replacement of used ultrasonic cleaning solutions. In some instances it is recommended that solution be drained and tanks thoroughly cleaned and dried after each ultrasonic cleaning cycle. many solutions available today are biodegradable, which facilitates disposal but local authorities should be consulted on proper practices.

The ultrasonic cleaner uses ultrasonic waves (vibration) using water with detergents or enzymatic products to break up soil and organic material on medical instruments/devices. These devices are rinsed then autoclaved (sterilized). The autoclave sterilizer uses heat, steam, and pressure to kill all pathogenic microorganisms and their spores.

Package Includes:

- 1 x Ultrasonic Transducers Plate
- 1 x Generator
- 1 x Manual

	skymen Skymer	1 Technology Corp	oration Limited
3	86-755-27094405	info@skymen.cc	skymenultrasonic.com
Floor 1st & 2nd, Buil	lding 3, Tanggang Taifeng I [Industrial Park, Dawangsh District, Shenzhen	an Community, Shajing Street, Bao'an