

SUS304 Submersible Ultrasonic Transducer Plate Flexible Tube 2400W

Basic Information

Place of Origin: ChinaBrand Name: Skymen

Certification: CE ROHS FCC SGS

Model Number: JTS-1048IMinimum Order Quantity: 1 unit

• Price: USD1120~1300 / SET

• Packaging Details: 1unit per carton / wooden case

Delivery Time: In StockPayment Terms: T/T

Supply Ability: 8000 pcs per month



Product Specification

Transducer Box: 1200*300*100mm
 Wire Methods: Rigid/flexible Tube
 Material: SUS304/SUS316

Fix Point: AvailableFlange: AvailableSuitable Tank Volume: 170~180L

Highlight: SUS304 Submersible Ultrasonic Transducer

Plate

, Flexible Tube Ultrasonic Transducer Plate, 2400W Ultrasonic Transducer Plate



Product Description

Submersible Ultrasonic transducer Box For Cleaning Fuel Pump Filter 2400W

Specification:

Model	JTS-1048I	
Transducer	48pcs	
Ultrasonic power	2400W	
Ultrasonic frequency	28/40Khz	
Ultrasonic box size (L*W*H)	1200*300*100MMmm	
Box weight	45KG	
Wiring out methods of box	Rigid or hose	
Fixed point on box	Available	
Flange to hang up on the tank wall	Available	
Make according to your drawing	Available	
Generator	1 set	
Generator weight	7KG	
Generator size	370*280*150	
Packing way	Packed by plywood case	
Double frequency	Available	
Sweeping frequency	Available	

Other size for your choice:

Other size for your choice:						
Model	Box size(mm)	Transduce r	Ultrasonic Power(W)	Frequency(KHz)	Wire Method	
JP-1006I	305*205*100	6pcs	300	28/40	Rigid tube/hose	
JP-1012I	355*305*100	12pcs	600	28/40	Rigid tube/hose	
JP-1018I	340*280*100	18pcs	900	28/40	Rigid tube/hose	
JP-1024I	430*280*100	24pcs	1200	28/40	Rigid tube/hose	
JP-1030I	460*370*100	30pcs	1500	28/40	Rigid tube/hose	
JP-1036I	550*450*100	36pcs	1800	28/40	Rigid tube/hose	
JP-1048I	600*450*100	48pcs	2400	28/40	Rigid tube/hose	
JTS-1030I	500*300*100	30pcs	1500	28/40	Rigid tube/hose	
JTS-1030I	600*250*100	30pcs	1500	28/40	Rigid tube/hose	
JTS-1036I	600*400*100	36pcs	1800	28/40	Rigid tube/hose	
JTS-1036I	700*400*100	36pcs	1800	28/40	Rigid tube/hose	
JTS-1036I	800*350*100	36pcs	1800	28/40	Rigid tube/hose	
JTS-1036I	900*300*100	36pcs	1800	28/40	Rigid tube/hose	
JTS-1036I	1000*300*100	36pcs	1800	28/40	Rigid tube/hose	
JTS-1048I	700*500*100	48pcs	2400	28/40	Rigid tube/hose	
JTS-1048I	800*500*100	48pcs	2400	28/40	Rigid tube/hose	
JTS-1048I	900*400*100	48pcs	2400	28/40	Rigid tube/hose	
JTS-1048I	1000*400*100	48pcs	2400	28/40	Rigid tube/hose	
JTS-1048I	1100*350*100	48pcs	2400	28/40	Rigid tube/hose	
JTS-1048I	1200*300*100	48pcs	2400	28/40	Rigid tube/hose	


- 1. The default frequency is 28/40KHz, if need other frequency(20/68/80/132KHz), then need to quote.
 2. Tank material is SUS304, if need SUS316, then price is 20% higher

- 3. There is no Skymen Logo for this series machine on sale, can put customer's logo, MOQ is 2pcs.4. This series machine is mainly for distributor to take up market.5. All the box can be put in water to working directly, customer needs to weld tank by himself.

Actual usage scenarios







Natural flavor extraction

Ultrasound has a significant effect on the extraction rate. Ultrasonic intensifies the supercritical fluid and extracts (SSFE) capsaicin from peppers.

The results of ultrasonic extraction of valerian spice and the results of extraction without ultrasonic were compared. The absorbance of the filtrate and the absorbance of the filtrate using ultrasonic was 12%-40% higher than that of the filtrate without ultrasonic.

food analysis

In the application of food analysis, ultrasonic extraction is also used for the pretreatment of food samples.



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen