

China

skymen

JP-4024GPH

Negotiation

100 units per month

In Stock

600W DPF Heated Ultrasonic Cleaner 38L Degreasing 99hrs Adjustable PSE

CE, ROHS, FCC, PSE, SGS, ISO9001

wooden case: 2650*1350*1250mm

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 Unit
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T
- Supply Ability:



Product Specification

Fuel:Tank Size:

• Use:

• Industry Used:

Heating Power:Cleaning Process:

Frequency:Tank Capacity:

• Highlight:

• Ultrasonic Power (w):

Electric 500x300x250 Mm All Industry Degreasing 1500W Hot Water Cleaning,Solvent Cleaning 600W 28KHz/40KHz 38L 600W DPF Heated Ultrasonic Cleaner, 99hrs Adjustable Heated Ultrasonic Cleaner,

PSE Degreasing Ultrasonic Cleaner

for more products please visit us on skymenultrasonic.com

Our Product Introduction

Product Description

4 Tanks Cleaning Rinsing Drying Function 28Khz 40Khz Ultrasonic Cleaning Machine

	Ultrasonic Frequency	40K Hz or 28KHz				
Specification	Material	Stainless Steel SUS 304				
	Tank thickness	2 mm				
	Ultrasonc Tank Capacity	38L				
	Rinsing Tank Capacity	38L				
	Drying tank capacity	38L				
	Timer	1~99Hours adjustable				
	Heater	20°C to 95°C adjustable				
	Machine voltage	AC 220V/380V, 3phases , Or other				
	Generator voltage	AC 110V/220V, 1phase				
	cleaning tank ultrasonic	600W				
	Rinsing tank ultrasonic	600W				
	Drying tank ultrasonic	/				
	Cleaning tank heater	1500W				
	Rinsing tank heater	1500W				
	Drying tank heater	3000W				
	Drain valve	1 inch				
Packing	Ultrasonic Tank Size	500*300*250mm (L x W x H)				
	Rinsing Tank size	500*300*250mm (L x W x H)				
	Drying Tank size	500*300*250mm (L x W x H)				
	Unit Size	2750*1100*1000mm				
	Package Size	Wooden case 3000*1350*1250mm				
	N.W. / G.W.	424 kg /530 kg				
	Warranty	1 year				



Our Product Introduction

Four tank coarse washing, filtering, rinsing, spraying and drying integrated equipment.

Model	Frequency (KHz)	Capacity (L)	Tank Size (MM)	Ultrasonic Power(W)	Heating Power(W)	Filtration System	Spray	Dry Power(W)		Heate (°C)
JP-4024GH	28/40	38	500*300*250	0-600	1500	YES	YES	3000	1-99	20-95
JP-4036GH	28/40	53	500*350*300	0-900	1500	YES	YES	3000	1-99	20-95
JP-4048GH	28/40	77	550*400*350	0-1200	3000	YES	YES	3000	1-99	20-95
JP-4060GH	28/40	99	550*450*400	0-1500	3000	YES	YES	3000	1-99	20-95
JP-4062GH	28/40	96	800*300*400	0-1500	3000	YES	YES	3000	1-99	20-95
JP-4072GH	28/40	135	600*500*450	0-1800	4500	YES	YES	3000	1-99	20-95
JP-4096GH	28/40	175	700*500*500	0-2400	6000	YES	YES	3000	1-99	20-95
JP-4120GH	28/40	264	800*600*550	0-3000	6000	YES	YES	3000	1-99	20-95
JP-4144GH	28/40	360	1000*600*600	0-3600	9000	YES	YES	6000	1-99	20-95
JP-4168GH	28/40	420	1500*700*400	0-4200	15000	YES	YES	6000	1-99	20-95
JP-4192GH	28/40	480	1200*500*800	0-4800	15000	YES	YES	9000	1-99	20-95
JP-4216GH	28/40	540	1000*900*600	0-5400	18000	YES	YES	9000	1-99	20-95
JP-4240GH	28/40	640	1000*800*800	0-6000	21000	YES	YES	9000	1-99	20-95
JP-4264GH	28/40	800	1000*1000*800	0-6600	24000	YES	YES	12000	1-99	20-95
JP-4288GH	28/40	960	1200*1000*800	0-7200	27000	YES	YES	12000	1-99	20-95
JP-4432GH	28/40	1500	1500*1000*1000	0-10800	27000	YES	YES	21000	1-99	20-95


Customized service: process plan design, frequency, power, size, etc. can be provided by Skymen technical engineering department tailored.

Equipment production process



skymen T

Raw Material



O Transducer Installation



Assembling



Board Cutting



6 Skymen Transducer Wiring



Tank Welding



1 Tank Polishing



Age Testing



Skymen Factory Shipping

