Our Product Introduction

38L Degreasing 600W Ultrasonic Cleaner 4 Tanks 28Khz 40Khz for cleaing engine block

Basic Information

Place of Origin: ChinaBrand Name: skymen

• Certification: CE, ROHS, FCC, PSE, SGS, ISO9001

Model Number: JP-4024GPHMinimum Order Quantity: 1 UnitPrice: Negotiation

• Packaging Details: wooden case: 2650*1350*1250mm

Delivery Time: In StockPayment Terms: T/T

Supply Ability: 100 units per month



Product Specification

• Fuel: Electric

Tank Size: 500x300x250 Mm
Industry Used: All Industry
Use: Degreasing
Heating Power: 1500W

Cleaning Process: Hot Water Cleaning, Solvent Cleaning

Ultrasonic Power (w): 600WFrequency: 28KHz/40KHz

• Tank Capacity: 38L

• Highlight: 40Khz Ultrasonic Cleaner,

4 Tanks Ultrasonic Cleaner, 28Khz Ultrasonic Cleaner

Product Description

4 Tanks Cleaning Rinsing Drying Function 28Khz 40Khz Ultrasonic Cleaning Machine

	Ultrasonic Frequency	40K Hz or 28KHz				
Specification	Material	Stainless Steel SUS 304				
	Tank thickness	2 mm				
	Ultrasonc Tank	38L				
	Capacity					
	Rinsing Tank Capacity					
	Drying tank capacity	38L				
	Timer	1~99Hours adjustable				
	Heater	20°C to 95°C adjustable				
	Machine voltage	AC 220V/380V, 3phases , Or other				
	Generator voltage	AC 110V/220V, 1phase				
	cleaning tank	600W				
	ultrasonic	00000				
	Rinsing tank ultrasonic	600W				
	Drying tank ultrasonic	V				
	Cleaning tank heater	1500W				
	Rinsing tank heater	1500W				
	Drying tank heater	3000W				
	Drain valve	1 inch				
Packing	Ultrasonic Tank Size	500*300*250mm (L x W x H)				
	Rinsing Tank size	500*300*250mm (L x W x H)				
	Drying Tank size	500*300*250mm (L x W x H)				
	Unit Size	2750*1100*1000mm				
	Package Size	Wooden case 3000*1350*1250mm				
	N.W. / G.W.	424 kg /530 kg				
	Warranty	1 year				



Four tank coarse washing, filtering, rinsing, spraying and drying integrated equipment.

Model	Frequency (KHz)	Capacity (L)	Tank Size (MM)	Ultrasonic Power(W)	Heating Power(W)	Filtration System	Spray	Dry Power(W)		Heater (°C)
JP-4024GH	28/40	38	500*300*250	0-600	1500	YES	YES	3000	1-99	20-95
JP-4036GH	28/40	53	500*350*300	0-900	1500	YES	YES	3000	1-99	20-95
JP-4048GH	28/40	77	550*400*350	0-1200	3000	YES	YES	3000	1-99	20-95
JP-4060GH	28/40	99	550*450*400	0-1500	3000	YES	YES	3000	1-99	20-95
JP-4062GH	28/40	96	800*300*400	0-1500	3000	YES	YES	3000	1-99	20-95
JP-4072GH	28/40	135	600*500*450	0-1800	4500	YES	YES	3000	1-99	20-95
JP-4096GH	28/40	175	700*500*500	0-2400	6000	YES	YES	3000	1-99	20-95
JP-4120GH	28/40	264	800*600*550	0-3000	6000	YES	YES	3000	1-99	20-95
JP-4144GH	28/40	360	1000*600*600	0-3600	9000	YES	YES	6000	1-99	20-95
JP-4168GH	28/40	420	1500*700*400	0-4200	15000	YES	YES	6000	1-99	20-95
JP-4192GH	28/40	480	1200*500*800	0-4800	15000	YES	YES	9000	1-99	20-95
JP-4216GH	28/40	540	1000*900*600	0-5400	18000	YES	YES	9000	1-99	20-95
JP-4240GH	28/40	640	1000*800*800	0-6000	21000	YES	YES	9000	1-99	20-95
JP-4264GH	28/40	800	1000*1000*800	0-6600	24000	YES	YES	12000	1-99	20-95
JP-4288GH	28/40	960	1200*1000*800	0-7200	27000	YES	YES	12000	1-99	20-95
JP-4432GH	28/40	1500	1500*1000*1000	0-10800	27000	YES	YES	21000	1-99	20-95

Customized service: process plan design, frequency, power, size, etc. can be provided by Skymen technical engineering department tailored.

Equipment production process





If you have any inquiry or problem, please directly contact me to know your need.



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com