## **Skymen Technology Corporation Limited** skymenultrasonic.com

## Timer Adjustable Ultrasonic Cleaning Equipment 600W 4 Tanks For Engine Cylinder with wash, rinse, spray, drying funciton

#### **Basic Information**

. Place of Origin: China Brand Name: skymen

CE, ROHS, FCC, PSE, SGS, ISO9001 · Certification:

Model Number: JP-4024GPH Minimum Order Quantity: 1 Unit • Price: Negotiation

· Packaging Details: wooden case: 2650\*1350\*1250mm

• Delivery Time: In Stock Payment Terms: T/T

. Supply Ability: 100 units per month



#### **Product Specification**

• Fuel: Electric

Tank Size: 500x300x250 Mm • Industry Used: All Industry

• Use: Degreasing . Heating Power: 1500W

Hot Water Cleaning, Solvent Cleaning . Cleaning Process:

600W Ultrasonic Power (w): • Frequency: 28KHz/40KHz

• Tank Capacity:

• Highlight: **Timer Adjustable Ultrasonic Cleaning** 

Equipments

600W Degreasing Ultrasonic Cleaning

Equipments

, Engine Cylinder Benchtop Ultrasonic Bath



#### More Images



### **Product Description**

4 Tanks Cleaning Rinsing Drying Function 28Khz 40Khz Ultrasonic Cleaning Machine

	Ultrasonic Frequency	40K Hz or 28KHz				
Specification	Material	Stainless Steel SUS 304				
	Tank thickness	2 mm				
	Ultrasonc Tank					
	Capacity	38L				
	Rinsing Tank Capacity	- 38L				
	Drying tank capacity	38L				
	Timer	1~99Hours adjustable				
	Heater	20°C to 95°C adjustable				
	Machine voltage	AC 220V/380V, 3phases , Or other				
	Generator voltage	AC 110V/220V, 1phase				
	cleaning tank	600W				
	ultrasonic					
	Rinsing tank ultrasonic	600W				
	Drying tank ultrasonic	/				
	Cleaning tank heater	1500W				
	Rinsing tank heater	1500W				
	Drying tank heater	3000W				
	Drain valve	1 inch				
Packing	Ultrasonic Tank Size	500*300*250mm ( L x W x H )				
	Rinsing Tank size	500*300*250mm ( L x W x H )				
	Drying Tank size	500*300*250mm ( L x W x H )				
	Unit Size	2750*1100*1000mm				
	Package Size	Wooden case 3000*1350*1250mm				
	N.W. / G.W.	424 kg /530 kg				
	Warranty	1 year				



# Four tank coarse washing, filtering, rinsing, spraying and drying integrated equipment.

Model	Frequency (KHz)	Capacity (L)	Tank Size (MM)	Ultrasonic Power(W)	Heating Power(W)	Filtration System	Spray	Dry Power(W)		Heater (°C)
JP-4024GH	28/40	38	500*300*250	0-600	1500	YES	YES	3000	1-99	20-95
JP-4036GH	28/40	53	500*350*300	0-900	1500	YES	YES	3000	1-99	20-95
JP-4048GH	28/40	77	550*400*350	0-1200	3000	YES	YES	3000	1-99	20-95
JP-4060GH	28/40	99	550*450*400	0-1500	3000	YES	YES	3000	1-99	20-95
JP-4062GH	28/40	96	800*300*400	0-1500	3000	YES	YES	3000	1-99	20-95
JP-4072GH	28/40	135	600*500*450	0-1800	4500	YES	YES	3000	1-99	20-95
JP-4096GH	28/40	175	700*500*500	0-2400	6000	YES	YES	3000	1-99	20-95
JP-4120GH	28/40	264	800*600*550	0-3000	6000	YES	YES	3000	1-99	20-95
JP-4144GH	28/40	360	1000*600*600	0-3600	9000	YES	YES	6000	1-99	20-95
JP-4168GH	28/40	420	1500*700*400	0-4200	15000	YES	YES	6000	1-99	20-95
JP-4192GH	28/40	480	1200*500*800	0-4800	15000	YES	YES	9000	1-99	20-95
JP-4216GH	28/40	540	1000*900*600	0-5400	18000	YES	YES	9000	1-99	20-95
JP-4240GH	28/40	640	1000*800*800	0-6000	21000	YES	YES	9000	1-99	20-95
JP-4264GH	28/40	800	1000*1000*800	0-6600	24000	YES	YES	12000	1-99	20-95
JP-4288GH	28/40	960	1200*1000*800	0-7200	27000	YES	YES	12000	1-99	20-95
JP-4432GH	28/40	1500	1500*1000*1000	0-10800	27000	YES	YES	21000	1-99	20-95

**Customized service:** process plan design, frequency, power, size, etc. can be provided by Skymen technical engineering department tailored.

## **Equipment production process**







#### **Skymen Technology Corporation Limited**



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen