

China

skymen

JP-5024GPH

Negotiation

100 units per month

In Stock

T/T

38L Degreasing 600W Ultrasonic Cleaner 5 Tanks 28Khz 40Khz for cleaing oil filter

CE, ROHS, FCC, PSE, SGS, ISO9001

wooden case: 2650*1350*1250mm

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 Unit
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

• Fuel:

• Use:

Tank Size:Industry Used:

Heating Power:Cleaning Process:

Frequency:Tank Capacity:

• Highlight:

• Ultrasonic Power (w):

Electric 500x300x250 Mm All Industry Degreasing 1500W Hot Water Cleaning,Solvent Cleaning 600W 28KHz/40KHz 38L

5 Tanks Ultrasonic Cleaner

Our Product Introduction

Product Description

5 Tanks Cleaning Rinsing Drying Function 28Khz 40Khz Ultrasonic Cleaning Machine

| | Ultrasonic Frequency | 40K Hz or 28KHz | | | | |
|---------------|-----------------------------|----------------------------------|--|--|--|--|
| Specification | Material | Stainless Steel SUS 304 | | | | |
| | Tank thickness | 2 mm | | | | |
| | Ultrasonc Tank Capacity | 38L | | | | |
| | Rinsing Tank Capacity | 38L | | | | |
| | Drying tank capacity | 38L | | | | |
| | Timer | 1~99Hours adjustable | | | | |
| | Heater | 20°C to 95°C adjustable | | | | |
| | Machine voltage | AC 220V/380V, 3phases , Or other | | | | |
| | Generator voltage | AC 110V/220V, 1phase | | | | |
| | cleaning tank ultrasonic | 600W | | | | |
| | Rinsing tank ultrasonic | 600W | | | | |
| | Drying tank ultrasonic | / | | | | |
| | Cleaning tank heater | 1500W | | | | |
| | Rinsing tank heater | 1500W | | | | |
| | Drying tank heater | 3000W | | | | |
| | Drain valve | 1 inch | | | | |
| Packing | Ultrasonic Tank Size | 500*300*250mm (L x W x H) | | | | |
| | Rinsing Tank size | 500*300*250mm (L x W x H) | | | | |
| | Drying Tank size | 500*300*250mm (L x W x H) | | | | |
| | Unit Size | 3400*1100*1000mm | | | | |
| | Package Size | Wooden case 3700*1350*1250mm | | | | |
| | N.W. / G.W. | 524 kg /630 kg | | | | |
| | Warranty | 1 year | | | | |

\kymen

Ultrasonic Cleaner. Skymen Made. Ultrasonic cleaning solution process service provider

Detail Specification

| Model | Frequency (KHz) | Capacity (L) | Tank Size (MM) | Ultrasonic Power(W) | Heating Power(W) | Spray/Lift/ Filtration | Dry Power(W) | | Heater (°C) | |
|------------|--------------------|-----------------|-------------------|------------------------|---------------------|---------------------------|-----------------|------|----------------|--|
| JP-5024GPH | 28/40 | 38 | 500*300*250 | 0-600 | 1500 | YES | 3000 | 1-99 | 20-95 | |
| JP-5036GPH | 28/40 | 53 | 500*350*300 | 0-900 | 1500 | YES | 3000 | 1-99 | 20-95 | |
| JP-5048GPH | 28/40 | 77 | 550*400*350 | 0-1200 | 3000 | YES | 3000 | 1-99 | 20-95 | |
| JP-5060GPH | 28/40 | 99 | 550*450*400 | 0-1500 | 3000 | YES | 3000 | 1-99 | 20-95 | |
| JP-5062GPH | 28/40 | 96 | 800*300*400 | 0-1500 | 3000 | YES | 3000 | 1-99 | 20-95 | |
| JP-5072GPH | 28/40 | 135 | 600*500*450 | 0-1800 | 4500 | YES | 3000 | 1-99 | 20-95 | |
| JP-5096GPH | 28/40 | 175 | 700*500*500 | 0-2400 | 6000 | YES | 3000 | 1-99 | 20-95 | |
| JP-5120GPH | 28/40 | 264 | 800*600*550 | 0-3000 | 6000 | YES | 3000 | 1-99 | 20-95 | |
| JP-5144GPH | 28/40 | 360 | 1000*600*600 | 0-3600 | 9000 | YES | 6000 | 1-99 | 20-95 | |
| JP-5168GPH | 28/40 | 420 | 1500*700*400 | 0-4200 | 15000 | YES | 6000 | 1-99 | 20-95 | |
| JP-5192GPH | 28/40 | 480 | 1200*500*800 | 0-4800 | 15000 | YES | 9000 | 1-99 | 20-95 | |
| JP-5216GPH | 28/40 | 540 | 1000*900*600 | 0-5400 | 18000 | YES | 9000 | 1-99 | 20-95 | |
| JP-5240GPH | 28/40 | 640 | 1000*800*800 | 0-6000 | 21000 | YES | 9000 | 1-99 | 20-95 | |
| JP-5264GPH | 28/40 | 800 | 1000*1000*800 | 0-6600 | 24000 | YES | 12000 | 1-99 | 20-95 | |
| JP-5288GPH | 28/40 | 960 | 1200*1000*800 | 0-7200 | 27000 | YES | 12000 | 1-99 | 20-95 | |
| JP-5432GPH | 28/40 | 1500 | 1500*1000*1000 | 0-10800 | 27000 | YES | 21000 | 1-99 | 20-95 | |

Customized service: process plan design, frequency, power, size, etc. can be provided by Skymen technical engineering department tailored.





