Skymen Technology Corporation Limited skymenultrasonic.com

SUS304 / 316 Immersible Ultrasonic Transducer Box 2400W For Ultrasonic Cleaner

Basic Information

. Place of Origin: China . Brand Name: Skymen CE, RoHS, ISO · Certification: JP-1048I Model Number: • Minimum Order Quantity: 1 set

• Price: Negotiation

packing by box or wooden case; the packing Packaging Details:

size decides by the machine

• Delivery Time:

• Payment Terms: Western Union, L/C, T/T, Paypal

. Supply Ability: 600 sets per month



Product Specification

JP-1048I Model: • Material: SUS316 304

• Warranty: 1 Year & Lifetime Technical Support

28/40kHz • Frequency:

· Purpose: Ultrasonic Cleaning

Silver · Color:

. Highlight: SUS 304 immersible ultrasonic transducer,

immersible ultrasonic transducer 2400W, Stainless Steel Ultrasonic Transducer Box



More Images



SUS304/316 Immersible Ultrasonic Transducer Box 2400W For Ultrasonic Cleaning

Ultrasonic Transducer Box technology extraction surpasses previous technical feasibility, obtains extraction more efficiently, is more effective than thermal extraction resident facility supervision, and reduces extraction time. Most pretreated material is extracted within 10 minutes

CAL	acted within 10 minutes.						
M o d el N o.	JP-1048I						
I m a g e							
_	Lilland and a Francisco	40 111-					
U ltr	Ultrasonic Frequency	40 kHz					
	Material	Stainless Steel SUS304					
	Timer	1~99min adjustable					
	Heater	N/A					
a	Degas	No					
s	Semiwave	No					
0		AC 100 ~ 120V, 50 / 60Hz					
ni	Power Supply	AC 220 ~ 240V, 50 / 60 Hz					
c m	Ultrasonic Power	0-2400W					
0	Transducer	18 pcs					
d	Basket& cover	No No					
el	Dasketa Cover						
	Tank Size	600*460*100 mm (L x W x H)					
	Max Power	2400W					
Р	Warranty	1 year					
a c ki n g							
F e at u r e s.	of cleaning requirements. 4. Integral bending forming, straight seam double-sided protective welding, small deformation and thorough leakage prevention.						
A p pl ic at io n.		Manufacture line,Electronics,Aerospace and marine parts, Machinery,Plating and Painting,Food industry					
C e rti fi c at e s	CE/ROHS/FCC/PSE/ISO2008 9001						

How does the Ultrasonic Transducer Box works?

generator is converted into high-frequency mechanical vibration through the converter and propagated into the medium. The flow of liquid creates tens of thousands of small air bubbles. Small air bubbles (cavitation nuclei) in the liquid vibrate under the action of the sound field. When the sound pressure reaches a certain value, the bubble grows rapidly and then closes quickly, making the bubble close. When the shock wave is generated, thousands of atmospheres of pressure are created around it, destroying the insoluble dirt and dispersing it in the cleaning fluid. When the group of particles is wrapped by oil and attached to the surface of the cleaning part, the oil is emulsified and the solid particles are separated, so as to achieve the purpose of cleaning the surface of the cleaning part.

Ultrasonic Transducer Box Specifications:

Model (JTM models)		JTM- 1006 JTM-1012		LIIM-1018		JTM- 1024	JTM- 1030	JTM-1036			
Ultrasonic	L	305	355	406		500	550	500			
transducer box	W	250	305	305		355	406	460			
size (mm)	Н	100	100	100		100	100	100			
Housing material	SUS304/SUS316L										
Surface finishing	Hard-Cr plating treatment (20+microns)										
Ultrasonic frequency	28KHz / 40KHz										
Ultrasonic transducers	6рс	s	12pcs		18pcs	24pcs	30pcs		36pcs		
Ultrasonic power	300)W	600W		900W	1200W	1500W		1800W		
Electronic	KG	300	KG600		KG900	KG1200	KG1500		KG1800		
generator	Ultrasonic generator work separately control transducers										
power suppy	AC 110V/220V or 220/240V, 1,13AMP										
*Custom made:68KHz/80KHz/120KHz and size are all available											

Ultrasonic Transducer Box's feature:

Original BLT type transducer

SUS stainless steel housing hard chrome plated (20+ microns)

Support continuous operation

Adjustable ultrasonic power Ultrasonic electronic generator with individual control

Custom sizes available

Transducer Number / Transducer Box: Range [6-40 per box]

Ultrasonic output: range [300W-2000W] Ultrasonic frequency: 28KHZ/40KHz

Features of underwater ultrasonic transducer generator:

Original BLT type transducer

SUS stainless steel housing hard chrome plated (20+ microns)

Support continuous operation

Sweep frequency ultrasonic generator

Humanized operation

Number of Transducers / Transducer Box: Range [6 to 36 per box] - Transducer box size can be customized

Ultrasonic output: range [300W~1800W] Ultrasonic frequency: 28KHZ/40KHz

Ultrasonic Transducer Box's Cleaning function

- 1. Ensure that the underwater transducers are manufactured to individual customer specifications and adjust the size and ultrasonic output to provide cleaning and processing results.
- 2. These underwater transducers provide excellent ultrasonic activity and can be easily controlled by Ultrawave's advanced technology.

Easy to install

The underwater sensor can be easily installed or retrofitted to existing tanks, allowing for easy service and maintenance while utilizing an upgraded system with ultrasonic cleaning technology.

Ultrasonic Transducer Box's hose tube


Industrial Transducer

- Strong work
- Low heat generation
- 📝 Stable output
- 📝 Long service life





Outlet Location Map







Outlet mode-hose diagram



Outlet methodhard tube diagram

Ultrasonic Transducer Box's Package Includes:

- 1 x Ultrasonic Transducer Box
- 1 x Generator
- 1 x Manual



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen