

General Lab Ultrasonic Cleaner Stainless Steel Ultrasonic Cleaning Unit

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Negotiation etails: 1sets/ wooden case

China

CE

1pcs

Skymen

JTS-1030

In Stock

600pcs per month

Ultrasonic Cleaner

Laboratory Instruments

- Packaging Details:
- Delivery Time:
- Payment Terms: Paypal / T/T / western Union
- Supply Ability:



Product Specification

- Product Name:
- Application:
- Capacity:
- Ultrasonic Power:
- Ultrasonic Frequency:
 - 28/40kHz Power Adjustable

100 Liter

1500W

- Feature:Highlight:
- ultrasonic cleaning device, ultrasonic washing machine, BLT transducer Lab Ultrasonic Cleaner

Our Product Introduction

Industrial Ultrasonic Cleaner For General Laboratory Instruments Cleaning

Competitive Advantage:

Material : SUS304/316L with 2mm thickness 15 years experience engineer will design the machine for you Filtration System: for heavy duty oil removing, cycle cleaning solvent, prevent second polution and better cleaning effects. PCB Board: manufactured by Skymen factory, more stable

Specifications:

JTS-1030

Tank's working dimension (mm):500*406*500(L*W*H) Overall dimension (mm):710*586*720 (L*W*H) Tank's total capacity: 101L Tank's material: SUS304 / SUS316L In-tank surface finishing: Hard-Cr Plating Treatment (20+ microns) Housing's material: Stainless steel Ultrasonic frequency: 28kHz / 40kHz Ultrasonic transducer: 30 Ultrasonic output power (MAX.): 1500W Electronic generator: KG1500 Heater's (hot plate) power: 4.5kW Cleaning tank's power requirement: AC 220V / 240V, 1, 25AMP

Description:

Adjustable ultrasonic power Original BLT type transducer SUS304/316L tank Adaptable for continuous operation Adjustable thermo controller Adjustable ultrasonic power With separate control ultrasonic electronic generator

Skymen JTS Series:

Skymen Model No.	JTS-1030	JTS-1036	JTS-1060	JTS-1072	JTS-1108	JTS - 114 4
TANK DIMENSION(mm)	500x406x500	500x460x550	700x650x650	1000x600x60	0 1000x900x600	120 0×1 000 ×80 0
OVERALL DIMENSION(mm)	680x586x850	680x640x900	900x850x1000	1200x800x95	0 1240x1140x950	144 0x1 240 x11 50
MAX. CAPACITY	101L	126L	295L	360L	540L	960 L
CONSTRUCTION CASE	SUS 304 (MIR	ROR SHINING	I IMAGE AVAILA	BLE)		
CONSTRUCTION TANK	SUS 304 / 316	ïL				
ULTRASONIC POWER(MAX.)	1500W	1800W	3000W	3600W 5400V	V 7200W	
ULTRASONIC FREQUENCY	28kHz/40kHz/	68kHz/80kHz/1	20kHz		·	
MAX. HEATING TEMP.	20~80C ADJU	STABLE				
HEATING POWER	зкw	4.5KW	6KW	9KW 12KW	24KW	
TIMER	0~30min adjus	table				
DRAIN	34" VALVE					
LID & BASKET	TAKE-OFF / S	TRUT LID; SU	S 304			
CLEANING TANK'S POWER REQUIREMENT	AC220V/380V	/415V/440V. 3				

GENERATOR'S					
POWER	AC110V/ 220V / 240V, 1				
REQUIREMENT					
GENERATOR	WITH SWEEP MODE AND REMOTE CONTROL				
FEATURES	MULTI-DIRECTION CASTORS WITH BRAKE;				
I LATONES	1 YEAR WARRANTY				
Optional	FILTRATION SYSTEM (PUMP, SUS FILTER,				
Optional	OIL CATCH CAN)				
	Skymen Technology Corporation Limited				

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen