



General Lab Ultrasonic Cleaner Stainless Steel Ultrasonic Cleaning Unit

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Sky men
- Certification: CE
- Model Number: JTS-1030
- Minimum Order Quantity: 1pc
- Price: Negotiation
- Packaging Details: 1sets/ wooden case
- Delivery Time: In Stock
- Payment Terms: Paypal / T/T / western Union
- Supply Ability: 600pcs per month



Product Specification

- Product Name: Ultrasonic Cleaner
- Application: Laboratory Instruments
- Capacity: 100 Liter
- Ultrasonic Power: 1500W
- Ultrasonic Frequency: 28/40kHz
- Feature: Power Adjustable
- Highlight: **ultrasonic cleaning device ,
ultrasonic washing machine ,
BLT transducer Lab Ultrasonic Cleaner**

for more products please visit us on skymenultrasonic.com

Product Description

Industrial Ultrasonic Cleaner For General Laboratory Instruments Cleaning

Competitive Advantage:

Material : SUS304/316L with 2mm thickness

15 years experience engineer will design the machine for you

Filtration System: for heavy duty oil removing, cycle cleaning solvent, prevent second pollution and better cleaning effects.

PCB Board: manufactured by Skymen factory, more stable

Specifications:

JTS-1030

Tank's working dimension (mm):500*406*500(L*W*H)

Overall dimension (mm):710*586*720 (L*W*H)

Tank's total capacity: 101L

Tank's material: SUS304 / SUS316L

In-tank surface finishing: Hard-Cr Plating Treatment (20+ microns)

Housing's material: Stainless steel

Ultrasonic frequency: 28kHz / 40kHz

Ultrasonic transducer: 30

Ultrasonic output power (MAX.): 1500W

Electronic generator: KG1500

Heater's (hot plate) power: 4.5kW

Cleaning tank's power requirement: AC 220V / 240V, 1, 25AMP

Description:

Adjustable ultrasonic power

Original BLT type transducer

SUS304/316L tank

Adaptable for continuous operation

Adjustable thermo controller

Adjustable ultrasonic power

With separate control ultrasonic electronic generator

Skymen JTS Series:

Skymen Model No.	JTS-1030	JTS-1036	JTS-1060	JTS-1072	JTS-1108	JTS-1144
TANK DIMENSION(mm)	500x406x500	500x460x550	700x650x650	1000x600x600	1000x900x600	1200x1140x950
OVERALL DIMENSION(mm)	680x586x850	680x640x900	900x850x1000	1200x800x950	1240x1140x950	1440x1140x950
MAX. CAPACITY	101L	126L	295L	360L	540L	960L
CONSTRUCTION CASE	SUS 304 (MIRROR SHINING IMAGE AVAILABLE)					
CONSTRUCTION TANK	SUS 304 / 316L					
ULTRASONIC POWER(MAX.)	1500W	1800W	3000W	3600W	5400W	7200W
ULTRASONIC FREQUENCY	28kHz/40kHz/68kHz/80kHz/120kHz					
MAX. HEATING TEMP.	20~80C ADJUSTABLE					
HEATING POWER	3KW	4.5KW	6KW	9KW	12KW	24KW
TIMER	0~30min adjustable					
DRAIN	¾" VALVE					
LID & BASKET	TAKE-OFF / STRUT LID; SUS 304					
CLEANING TANK'S POWER REQUIREMENT	AC220V/380V/415V/440V. 3					

GENERATOR'S POWER REQUIREMENT	AC110V/ 220V / 240V, 1
GENERATOR	WITH SWEEP MODE AND REMOTE CONTROL
FEATURES	MULTI-DIRECTION CASTORS WITH BRAKE; 1 YEAR WARRANTY
Optional	FILTRATION SYSTEM (PUMP, SUS FILTER, OIL CATCH CAN)



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen