Our Product Introduction



Skymen Ultrasonic Cleaning Machine Oil Filtration And Pneumatic Lift

Basic Information

. Place of Origin: China . Brand Name: Skymen CE · Certification: JTS-1060 Model Number: • Minimum Order Quantity: 1set

• Price: Negotiation

 Packaging Details: 1sets/ wooden case

• Delivery Time: In Stock

Payment Terms: Paypal / T/T / western Union

. Supply Ability: 600pcs per month





Product Specification

• Product Name: Ultrasonic Cleaner

· Application: Heavy Oil And Carbon Removing

300 Liter • Capacity: Ultrasonic Power: 3000W • Ultrasonic Frequency: 28/40kHz • Timer: 1~99 Hours Feature: Power Adjustable

Standard:

• Highlight: dual frequency ultrasonic cleaner,

ultrasonic cleaning unit

Product Description

Ultrasonic Cleaning Machine Oil Filtration And Pneumatic Lift

Skymen ultrasonic cleaning machine with oil filtration to skim oil from heavily dirty objects. With pneumatic lift to avoid workers from heavy goods.

Description:

Adjustable ultrasonic power Original BLT type transducer

SUS304/316L tank

Adaptable for continuous operation

Adjustable thermo controller

Adjustable ultrasonic power

With separate control ultrasonic electronic generator

Sweep mode control available

Digital timer control

Boost mode& oil skimmer upon client's requirement

Pressure pump and filter system

With pneumatic lift to up and down goods.

Competitive Advantage:

Material: SUS304/316L with 2mm thickness

15 years experience engineer will design the machine for you

Filtration System: for heavy duty oil removing, cycle cleaning solvent, prevent second polution and

better cleaning effects.

PCB Board: manufactured by Skymen factory, more stable

Specifications:

| Model | JTS-1060 | | | | |
|--------------------------------|---|--|--|--|--|
| Tank's working dimension (mm) | 700*650*650(L*W*H) | | | | |
| Overall dimension (mm) | 900*850*1000(L*W*H) | | | | |
| Tank's total capacity | 300L | | | | |
| Tank's material | SUS304 / SUS316 | | | | |
| In-tank surface finishing | Hard-Cr Plating Treatment (20+ microns) | | | | |
| Housing's material | Stainless steel | | | | |
| Ultrasonic frequency | 28kHz / 40kHz | | | | |
| Ultrasonic transducer | 60pcs | | | | |
| Ultrasonic output power (MAX.) | 3000W | | | | |
| Electronic generator | KG3000 | | | | |
| Heater's (hot plate) power | 9KW | | | | |

Skymen JTS Series:

| Skymen Model No. | JTS-1030 | JTS-1036 | JTS-1060 | JTS-10 | JTS-1072 JT | | JTS-1108 | | |
|--------------------------|--|-------------|--------------|--------------|------------------|---------------|--------------|--------------------------------|--|
| TANK DIMENSION(mm) | 500x406x500 | 500x460x550 | 700x650x650 | 1000x6 | 1000x600x600 100 | | 1000x900x600 | | |
| OVERALL DIMENSION(mm) | 680x586x850 | 680x640x900 | 900x850x1000 | 1200x800x950 | | 1240x1140x950 | | 144 0x1 240 x11 50 | |
| MAX. CAPACITY | 101L | 126L | 295L | 360L | 360L 540L | | | 960 L | |
| CONSTRUCTION CASE | SUS 304 (MIRROR SHINING IMAGE AVAILABLE) | | | | | | | | |
| CONSTRUCTION TANK | SUS 304 / 316L | | | | | | | | |
| ULTRASONIC POWER(MAX.) | 1500W | 1800W | 3000W | 3600W | 5400W | | 7200W | | |
| ULTRASONIC FREQUENCY | 28kHz/40kHz/68kHz/80kHz/120kHz | | | | | | | | |
| MAX. HEATING TEMP. | 20~80C ADJUSTABLE | | | | | | | | |
| HEATING POWER | 3KW | 4.5KW | 6KW | 9KW | 12KW | | 24KW | | |
| TIMER | 0~30min adjustable | | | | | | | | |
| DRAIN | %" VALVE | | | | | | | | |
| LID & BASKET | TAKE-OFF / STRUT LID; SUS 304 | | | | | | | | |

| CLEANING TANK'S POWER REQUIREMENT | AC220V/380V/415V/440V. 3 |
|---|--|
| GENERATOR'S POWER REQUIREMENT | AC110V/ 220V / 240V, 1 |
| GENERATOR | WITH SWEEP MODE AND REMOTE CONTROL |
| FEATURES | MULTI-DIRECTION CASTORS WITH BRAKE; 1 YEAR WARRANTY |
| Optional | FILTRATION SYSTEM (PUMP, SUS FILTER, OIL CATCH CAN) |



Skymen Technology Corporation Limited



86-755-27094405



info@skymen.cc



skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen