

Large Ultrasonic Cleaning Machine / Automotive Ultrasonic Cleaner For Cylinder

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Negotiation • Packaging Details: 1sets/ wooden case
- Delivery Time:
- In Stock

600pcs per month

Ultrasonic Cleaner

198 Liter

China

CE

1pcs

Skymen

JTS-1048

- Payment Terms: Paypal / T/T / western Union
- Supply Ability:



 \mathbf{S}

Product Specification

- Product Name:
- Application:
- Capacity:
- Ultrasonic Power:
- Ultrasonic Frequency:
- Timer:
- Feature:
- Standard:
- Highlight:
- 2400W 28/40kHz 1~99 Hours Power Adjustable

Engine And Cylinder Cleaning

- CE
 - dual frequency ultrasonic cleaner, ultrasonic washing machine

Our Product Introduction

Large Capacity Ultrasonic Cleaning Machine For Cylinder

Applications:

Ultrasonic cleaneing machine for cylinder head clean with high efficiency. Tank size can be made based on customer requirement.

Description:

Adjustable ultrasonic power Original BLT type transducer SUS304/316L tank Adaptable for continuous operation Adjustable thermo controller Adjustable ultrasonic power With separate control ultrasonic electronic generator Sweep mode control ultrasonic electronic generator Sweep mode control ultrasonic electronic generator Sweep mode control ultrasonic electronic generator Pigital timer control Boost mode& oil skimmer upon client's requirement Pressure pump and filter system are available Specifications:

Model	JTS-1048
Tank's working dimension (mm)	600*550*600(L*W*H)
Overall dimension (mm)	690*740*950(L*W*H)
Tank's total capacity	198L
Tank's material	SUS304 / SUS316
In-tank surface finishing	Hard-Cr Plating Treatment (20+ microns)
Housing's material	Stainless steel
Ultrasonic frequency	28kHz / 40kHz
Ultrasonic transducer	48pcs
Ultrasonic output power (MAX.)	2400W
Electronic generator	KG2400
Heater's (hot plate) power	6KW

Skymen JTS Series:

Skymen Model No.	JTS-1030	JTS-1036	JTS-1060	JTS-1072		JTS-1108	JTS - 114 4		
TANK DIMENSION(mm)	500x406x500	500x460x550	700x650x650	1000×6	00×600	1000x900x600	120 0x1 000 x80 0		
OVERALL DIMENSION(mm)	680x586x850	680x640x900	900x850x1000	1200x800x950		1240x1140x950	144 0x1 240 x11 50		
MAX. CAPACITY	101L	126L	295L	360L		540L	960 L		
CONSTRUCTION CASE	SUS 304 (MIRROR SHINING IMAGE AVAILABLE)								
CONSTRUCTION TANK	SUS 304 / 316L								
ULTRASONIC POWER(MAX.)	1500W	1800W	3000W	3600W	5400W	7200W			
ULTRASONIC FREQUENCY	28kHz/40kHz/68kHz/80kHz/120kHz								
MAX. HEATING TEMP.	20~80C ADJUSTABLE								
HEATING POWER	зкw	4.5KW	6KW	9KW	12KW	24KW			
TIMER	0~30min adjustable								
DRAIN	3/4" VALVE								
LID & BASKET	TAKE-OFF / S	TRUT LID; SU	S 304						
CLEANING TANK'S POWER REQUIREMENT	AC220V/380V/415V/440V. 3								
GENERATOR'S POWER REQUIREMENT	AC110V/ 220\	/ / 240V, 1							

GENERATOR	WITH SWEEP MODE AND REMOTE CONTROL		
FEATURES	MULTI-DIRECTION CASTORS WITH BRAKE; 1 YEAR WARRANTY		
Optional	FILTRATION SYSTEM (PUMP, SUS FILTER, OIL CATCH CAN)		

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen