

Cleaning Auto Parst Engine Block Spray Cleaning Machine High Pressure

Basic Information

- Place of Origin:
- China • Brand Name: Skymen • Certification: ISO 9001, ISO14001, CE, FCC, BSCI,etc. JP-0900P Model Number: • Minimum Order 1 Quantity: • Price: \$2000-\$5000/pc • Packaging Details: Export special wooden box • Delivery Time: 20-30 working days T/T, Western Union, MoneyGram • Payment Terms: • Supply Ability: 10000pcs per month



-


Product Specification

Model:	JP-0900P
• model.	01 00001
Cleaning Method:	High Pressure Spraying
Basket Diameter:	900mm
Work Space Height:	500mm
Basket Load-bearing:	250KG(can Be Customized)
Rotating Speed:	10~50R/MIN
Water Pump Power:	1.5KW
Sub-Tank Capacity:	130L
Basket Rotation Drive:	Motor/0.15kw
Heating Power:	6KW
Highlight:	Auto Parts Spray Cleaning Machine, High Pressure Spray Cleaning Machine,

Engine Block Spraying Cleaning Machine



More Images



Product Description:

The high-pressure rotary basket spray cleaning machine uses high-pressure jets and centrifugal principles generated by high-temperature hot water during rapid rotation to quickly peel off dirt on the inner and outer surfaces of the workpiece to achieve the purpose of thorough cleaning.

The control part adopts a programmable controller with a high degree of automation. It is a cleaning equipment that reduces the labor intensity of workers, is efficient, energy-saving, safe and environmentally friendly.

Technical Parameters:

Product Name:	Spraying Cleaning Machine with Rotary Basket
Model:	JP-0900P
Cleaning Method:	High Pressure Spraying
Basket	900mm
Work Space Height:	500mm
Basket Load-bearing:	350KG (can Be Customized)
Water Pump Power:	1.5KW
Spray Pressure:	2.5-3 Bar Adjustable
Basket Rotation Drive:	Motor/0.37KW
Sub-Tank Capacity:	130L
Rotating Speed:	10~50R/MIN adjustable

Hot selling models

Spraying Cleaning Machine With Rotating Basket										
Model	Basket Diamete r	Work Space Height	Cavity Material	Basket Load- bearing	Basket Rotation Drive	Rotating Speed (R/MIN)	Sub- Tank Capac ity	Heating Power	Water Pump Power	Spray Pressu (Bar)
JP-0500ZP	500mm	300mm	SUS304/1.5 MM	50kg	Spray drives rotation	-	40L	3KW	0.55KW	2.5
JP-0600ZP	600mm	350mm	SUS304/1.5 MM	50kg	Spray drives rotation	-	65L	3KW	0.55KW	2.5
JP-0500P	500mm	300mm	SUS304/1.5 MM	80kg	Motor/0.15kw	10~50	50L	ЗКW	0.55KW	2.5
JP-0600P	600mm	350mm	SUS304/1.5 MM	80kg	Motor/0.15kw	10~50	70L	3KW	0.55KW	2.5 3
JP-0700P	700mm	350mm	SUS304/1.5 MM	80kg	Motor/0.15kw	10~50	85L	3KW	0.75KW	2.5 3
JP-0800P	800mm	500mm	SUS304/2.0 MM	250kg	Motor/0.15kw	10~50	100L	6KW	0.75KW	2.5 3
JP-0900P	900mm	500mm	SUS304/2.0 MM	250kg	Motor/0.15kw	10~50	130L	6KW	1.5KW	2.5 3
JP-1000P	1000m m	720mm	SUS304/2.0 MM	250kg	Motor/0.37kw	10~50	145L	6KW	2.2KW	35
JP-1200P	1200m m	730mm	SUS304/2.0 MM	350kg	Motor/0.37kw	10~50	160L	9KW	2.2KW	35
JP-1500P	1500m m	850mm	SUS304/2.0 MM	400kg	Motor/0.55kw	10~50	200L	9KW	3KW	35
JP-2000P	2000m m	1000mm	SUS304/2.0 MM	600kg	Motor/0.75kw	10~50	450L	12KW	3KW	35

Highly equipped with automatic switch cover and PLC control

Note: Customization of high-pressure rotary spray cleaning machines of different sizes is supported. Please consult customer service for details.

Product Name: Spraying Cleaning Machine Rotating Speed : 10~50R/MIN Cleaning Method: High Pressure Spraying Tank Material: SUS304 Basket Diameter: 900mm Model: JP-0900P Designed for cleaning cylinder heads and engine blocks High pressure spraying for efficient and thorough cleaning Constructed with durable and corrosion-resistant SUS304 material Large basket diameter of 1000mm for cleaning various car parts Model JP-0900P specifically designed for car parts cleaning

Advantages of the Rotary Basket High Pressure Water Spraying Cleaning Machine

One-touch operation, adjustable spray pressure 720° cleaning without dead ends Large cleaning batches, saving labor Liquid real-time circulation filtration system to improve liquid utilization efficiency Equipment has low energy consumption and low noise The high-pressure spray cleaning machine can clean workpieces in batches with high efficiency and uniform effect. Strong controllability and low cost

Operating procedures of Rotary Basket High Pressure Water Spraying Cleaning Machine

Open the upper cover and place the workpiece on the turntable;

Set spray cleaning time;

Turn on the device start button, and the device will enter the automatic cleaning state. After cleaning, the device will automatically

Stop moving;

Open the upper cover and manually unload the material

The Spraying Cleaning Machine is suitable for a variety of industrial cleaning applications, including but not limited to

- Cylinder block cleaning machine for automotive and heavy-duty engines
- Cleaning of metal parts in manufacturing plants
- Degreasing and cleaning of industrial equipment and machinery
- Removal of contaminants from metal surfaces in machining processes
- Cleaning of engine components in automotive and aerospace industries
- Surface preparation before painting or coating
- Cleaning of parts in the food, pharmaceutical, and chemical industries
- And many more industrial cleaning applications

More Details



High Pressure Spray Device

The high-pressure water pump is used to pressurize the cleaning fluid to form a high-speed, high-pressure jet that impacts metal shavings, dust, cutting fluid, grease, etc. on the surface of the workpiece to separate the dirt and achieve the purpose of cleaning.





<



Button Control

Simple, intuitive, and easy to operate, with an emergency button that can be quickly cut off in special situations.

*Customizable PLC+touch screen control.



Stainless Steel Body

High temperature resistance, oxidation resistance, acid & alkali corrosion resistance, with long service life.



Circulation Filtration System

Micron-level filter effectively filters floating oil dirt and particles, reducing the frequency of cleaning fluid replacement.

Sealed Silencer Lid

Equipped with a gas strut to assist in opening and closing, so that the lid can open easily and close tightly.

Silicone Sealing Strip

Fits tightly to the edge of the lid, prevents liquid leakage, eliminates noise.

*Optional configuration: transparent observation window + internal LED lighting for easy observation of cleaning conditions.



Manual Hydraulic Gun (optional)

Manual assisted cleaning, suitable for special structure of the workpiece, improve the cleaning effect.

Manual Air Gun (optional)

Can be connected to an air compressor to quickly blow away residual liquid on the surface and speed up the drying of the workpiece.



Fixed Foot Stand


(<

Made of high-strength material, stable and reliable.

Flexible Universal Wheel

Flexible steering makes it easy to push, and the equipment can be easily moved to the required position, improving maneuverability.





info@skymen.cc

86-755-27094405

Skymenultrasonic.com

Floor 1st & 2nd, Building 3, Tanggang Taifeng Industrial Park, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen