

## Ultrasonic Cylinder Head Cleaning Machine Filter System Motor Oil Cleaning

Our Product Introduction

for more products please visit us on [skymenultrasonic.com](http://skymenultrasonic.com)

### Basic Information

- Place of Origin: China
- Brand Name: skyman
- Certification: CE
- Model Number: JTS-1060
- Minimum Order Quantity: 1
- Price: Negotiation
- Packaging Details: 1 pcs / wooden case packing
- Delivery Time: In Stock
- Payment Terms: T/T, Western Union
- Supply Ability: 100 /month



### Product Specification

- Material: Stainless Steel SUS304/316L
- Use: Cleaning , Degreasing
- Control: Separate Generator
- Optional: Oil Filter System
- Special: Multi Tank
- Ultrasonic Frequency: 28khz/40khz
- Ultrasonic Power: 7200W
- Power: Adjustable Ultrasonic Power
- Heater: 20 To 80 Asjudt
- Highlight: **dual frequency ultrasonic cleaner, ultrasonic washing machine**



## Product Description

Ultrasonic Cylinder Head Cleaning Machine Filter System Motor Oil Cleaning

The machine is customized and certified with CE.  
If need, rising tank or drying tank is optional based on customer's needs.  
Large Capacity for Diesel Particulate Filter Cleaning

### Applications:

Skymen Dual frequency ultrasonic cleaner can be use for car parts washing, engine block degrease, radiator clean, also can clean electronic parts. No damage to object surface and improve cleaning efficiency.

### Description:

Adjustable ultrasonic power  
Original BLT type transducer  
SUS304/316L tank  
Adaptable for continuous operation  
Adjustable thermo controller  
Adjustable ultrasonic power  
With separate control ultrasonic electronic generator  
Sweep mode control available  
Digital timer control  
Boost mode& oil skimmer upon client's requirement  
Pressure pump and filter system  
With pneumatic lift to up and down goods.

### Product Description

| Model: Skymen™                 | JTS-1012                                  | JTS-1018 | JTS-1024 | JTS-1030 | JTS-1036 | JTS-1072 |      |
|--------------------------------|---|----------|----------|----------|----------|----------|------|
| TANK'S WORKING DIMENSION (mm)  | L1  | 355      | 406      | 500      | 500      | 500      | 1110 |
|                                | W1  | 305      | 305      | 355      | 406      | 460      | 600  |
|                                | H1  | 355      | 460      | 500      | 500      | 550      | 600  |
| OVERALL DIMENSION (mm)         | L2  | 535      | 586      | 680      | 710      | 710      | 1320 |
|                                | W2  | 485      | 485      | 535      | 586      | 640      | 780  |
|                                | H2  | 750      | 680      | 720      | 720      | 770      | 820  |
| TANK'S TOTAL CAPACITY          | 38L                                       | 56L      | 88L      | 101L     | 126L     | 369L     |      |
| TANK'S MATERIAL                | SUS304 / SUS316L                          |          |          |          |          |          |      |
| IN-TANK SURFACE FINISHING      | Hard-Cr Plating Treatment ( 20+ microns ) |          |          |          |          |          |      |
| HOUSING'S MATERIAL             | Stainless steel                           |          |          |          |          |          |      |
| ULTRASONIC FREQUENCY*          | 28kHz / 40kHz                             |          |          |          |          |          |      |
| ULTRASONIC TRANSDUCER          | 12  | 18       | 24       | 30       | 36       | 72       |      |
| ULTRASONIC OUTPUT POWER (MAX.) | 600W                                      | 900W     | 1200W    | 1500W    | 1800W    | 3600W    |      |
| ELECTRONIC GENERATOR           | KG600                                     | KG900    | KG1200   | KG1500   | KG1800   | KG3600   |      |
|                                | Build-in                                  |          | Separate |          |          |          |      |
| HEATER'S (HOT PLATE) POWER     | 1.5kW                                     | 3kW      |          | 4.5kW    | 9KW      |          |      |

### Package

|                                  |                                |
|----------------------------------|--------------------------------|
| Packing , loading, delivery time |                                |
| Packing unit                     | 1set/wooden case               |
| Packing method                   | Export wooden case             |
| Loading port                     | Shenzhen                       |
| Delivery time                    | About 15 working days          |
| Minimum Order Quantity           | 1set                           |
| Transport method                 | By express company / air / sea |

### Competitive Advantage:

Material : SUS304/316L with 2mm thickness  
15 years experience engineer will design the machine for you  
Filtration System: for heavy duty oil removing, cycle cleaning solvent, prevent second pollution and better cleaning effects.  
PCB Board: manufactured by Skymen factory, more stable



+86 13528763370



sales3@skymen.cc



skymenultrasonic.com