

# Ultrasonic Cylinder Head Cleaning Machine Filter System Motor Oil Cleaning

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- Negotiation 1pcs / wooden case packing In Stock
- T/T, Western Union

100 /month

China

skymen

JTS-1060

CE

1



# **Product Specification**

• Material:

• Use:

• Control:

• Optional:

• Special:

Power:

• Heater:

• Highlight:

• Ultrasonic Power:

- Stainless Steel SUS304/316L
- Cleaning, Degreasing
- Separate Generator
  - Oil Filter System
- Multi Tank
- 28khz/40khz • Ultrasonic Frequency:
  - 7200W
    - Adjustable Ultrasonic Power
    - 20 To 80 Asjudt
      - dual frequency ultrasonic cleaner, ultrasonic washing machine



## **Product Description**

Ultrasonic Cylinder Head Cleaning Machine Filter System Motor Oil Cleaning

The machine is customized and certified with CE. If need, rising tank or drying tank is optional based on customer's needs. Large Capacity for Diesel Particulate Filter Cleaning

#### **Applications:**

Skymen Dual frequency ultrasonic cleaner can be use for car parts washing, engine block degrease, radiator clean, also can clean electronic parts. No damage to object surface and improve cleaning efficiency.

### Description:

Adjustable ultrasonic power Original BLT type transducer SUS304/316L tank Adaptable for continuous operation Adjustable thermo controller Adjustable ultrasonic power With separate control ultrasonic electronic generator Sweep mode control available Digital timer control Boost mode& oil skimmer upon client's requirement Pressure pump and filter system With pneumatic lift to up and down goods.

#### **Product Description**

Model: Skymen™		JTS- 1012	JTS-	1018	JTS- 1024	JTS- 1030	JTS- 1036	JTS- 1072
TANK'S WORKING DIMENSION (mm)	L1	355	406		500	500	500	1110
	W1	305	305		355	406	460	600
	H1	355	460		500	500	550	600
OVERALL DIMENSION (mm)	L2	535	586		680	710	710	1320
	W2	485	485		535	586	640	780
	H2	750	680		720	720	770	820
TANK'S TOTAL CAPACITY		38L	56L		88L	101L	126L	369L
TANK'S MATERIAL		SUS304 / SUS316L						
IN-TANK SURFACE FINISHING		Hard-Cr Plating Treatment ( 20+ microns )						
HOUSING'S MATERIAL		Stainless steel						
ULTRASONIC FREQUENCY*		28kHz / 40kHz						
ULTRASONIC TRANSDUCER		12	18		24	30	36	72
ULTRASONIC OUTPUT POWER (MAX.)		600W	900W		1200W	1500W	1800W	3600W
ELECTRONIC GENERATOR		KG600	KG900		KG120 0	KG150 0	KG180 0	KG3600
		Build-in Separate						
HEATER'S (HOT PLATE) POWER		1.5kW		3kW			4.5kW	экw

#### Package

Packing , loading, delivery time					
Packing unit	1set/wooden case				
Packing method	Export wooden case				
Loading port	Shenzhen				
Delivery time	About 15 working days				
Minimum Order Quantity	1set				
Transport method	By express company / air / sea				

### **Competitive Advantage:**

Material : SUS304/316L with 2mm thickness

15 years experience engineer will design the machine for you

Filtration System: for heavy duty oil removing, cycle cleaning solvent, prevent second polution and better cleaning effects.

PCB Board: manufactured by Skymen factory, more stable

skymen Technology Corporation Limited						
Q	86-755-27094405	info@skymen.cc	skymenultrasonic.com			
Floor 1st & 2nd, Bu	uilding 3, Tanggang Taifen	JIndustrial Park, Dawangs District, Shenzhen	han Community, Shajing Street, Bao'an			